

## DAFTAR PUSTAKA DAN LAMPIRAN

- Atmel, 2014. *ATmega16A 8-bit Microcontroller with 16K Bytes In-System Programmable Flash*, San Jose: Atmel Semiconductor Manufacturing Company.
- Atmel, 2010. *with 16K Bytes Programmable ATmega16 ( L )*, San Jose, California, United States: Atmel Semiconductor Manufacturing Company.
- Bakhshpour, M. et al., 2017. Microcontact imprinted quartz crystal microbalance nanosensor for protein C recognition. *Colloids and Surfaces B: Biointerfaces*, 151, pp.264–270. Available at: <http://linkinghub.elsevier.com/retrieve/pii/S0927776516308591>.
- Berger, A.S., 2005. *Hardware and Computer Organization ( Embedded Technology )*, Amsterdam, Netherlands: Elsevier, 2005.
- Han, Y., Zheng, W. & Su, D., 2014. Suppressing the frequency jump in quartz crystal microbalance. *Proceedings of the 2014 Symposium on Piezoelectricity, Acoustic Waves, and Device Applications*, pp.218–221.
- Ishay, R. Ben et al., 2015. Real time acoustic profiling of a live cancerous cell monolayer using QCM. *Sensors and Actuators, B: Chemical*, 215, pp.373–381.
- Jaruwongrungrsee, K. et al., 2007. Quartz crystal microbalance humidity sensor using electrospun PANI micro/nano dots. *2007 7th IEEE International Conference on Nanotechnology - IEEE-NANO 2007, Proceedings*, pp.316–319.
- Jin, H. et al., 2016. A humidity sensor based on quartz crystal microbalance using graphene oxide as a sensitive layer. *Vacuum*, pp.1–5. Available at: <http://linkinghub.elsevier.com/retrieve/pii/S0042207X16307126>.
- Kagiyama, S. et al., 2015. Detection of Influenza Virus Subtype Using Quartz Crystal Microbalance. , pp.2–3.
- Malvino, A. & Bates, D.J., 2016. *Electronic Principles*,
- Maxim, 2015. *DS 1364 x 8 , Serial , I C Real-Time Clock*, San Jose: Maxim Integrated.
- NXP, 2005. *74HC393, 74HCT393 Dual 4-bit binary ripple counter*, Eindhoven: NXP Semiconductor.
- NXP, 2008. *74HC4020; 74HCT4020 14-stage binary ripple counter with oscillator*, Eindhoven: NXP Semiconductor.
- NXP, 2016a. *74HC4024 7-stage binary ripple counter*, Eindhoven: NXP

Semiconductor.

NXP, 2014. *74HC4040; 74HCT4040 12-stage binary ripple counter*, Eindhoven: NXP Semiconductor.

NXP, 2016b. *74HC4051; 74HCT4051 8-channel analog multiplexer/demultiplexer*, Eindhoven, Netherlands: NXP Semiconductor.

NXP, 2016c. *74HC573; 74HCT573 Octal D-type transparent latch; 3-state*, Eindhoven, Netherlands: NXP Semiconductor.

Ogata, K., 1987. *Discrete-time Control Systems Prentice Hall International editions 2*, illustr ed., New Jersey: Prentice-Hall International, 1995.

Ogimoto, Y. et al., 2015. Detection of ammonia in human breath using quartz crystal microbalance sensors with functionalized mesoporous SiO<sub>2</sub> nanoparticle films. *Sensors and Actuators B: Chemical*, 215, pp.428–436. Available at: <http://dx.doi.org/10.1016/j.snb.2015.03.103>.

Pali, M. et al., 2017. Detection of Fish Hormones by Electrochemical Impedance Spectroscopy and Quartz Crystal Microbalance. *Sensing and Bio-Sensing Research*, 13, pp.1–8. Available at: <http://dx.doi.org/10.1016/j.sbsr.2017.01.001>.

Saad, N.A. et al., 2014. Quartz crystal microbalance for bacteria application review. *2014 2nd International Conference on Electronic Design (ICED)*, pp.455–460. Available at: <http://ieeexplore.ieee.org/lpdocs/epic03/wrapper.htm?arnumber=7015849>.

Yurish, S.Y., 2007. Intelligent Data Acquisition System for Quartz Crystal Microbalance and Other Resonator-Based Sensors. *IEEE International Workshop on Intelligent Data Acquisition and Advanced Computing Systems: Technology and Applications*, (September), pp.2–7.