

## REFERENSI

- [1] P. S. Almeida, H. A. C. Braga, M. A. Dalla Costa, and J. M. Alonso, "Offline soft-switched LED driver based on an integrated bridgeless boost-asymmetrical half-bridge converter," *IEEE Trans. Ind. Appl.*, vol. 51, no. 1, pp. 761–769, 2015.
- [2] A. Gago Calderón, L. Narvarte Fernández, L. M. Carrasco Moreno, and J. Serón Barba, "LED bulbs technical specification and testing procedure for solar home systems," *Renew. Sustain. Energy Rev.*, vol. 41, pp. 506–520, 2015.
- [3] R. A. A. El-wahab and K. Tetranychus, "Light Emitting Diodes (LEDs) Reduce Vertimec, Resistance in Tetranychusurticae (Koch)," *IJCBS Res. Pap.*, vol. 1, no. 3, pp. 28–40, 2014.
- [4] A. T. L. Lee, J. K. O. Sin, and P. C. H. Chan, "Scalability of Quasi-Hysteretic FSM-Based Digitally Controlled Single-Inductor Dual-String Buck LED Driver to Multiple Strings," *IEEE Trans. Power Electron.*, vol. 29, no. 1, pp. 501–513, Jan. 2014.
- [5] Y. C. Tsai, T. J. Liang, K. H. Chen, and L. P. Y. Ting, "Design and implementation of single-stage LED driver with high frequency pulse," in *2nd International Future Energy Electronics Conference, IFEEEC 2015*, 2015, pp. 1–6.
- [6] C. Y. Hsu and Y. L. Chang, "A single stage single switch valley switching Flyback-Forward converter with regenerative snubber and PFC for LED light source system," *Proc. 2014 Int. Conf. Intell. Green Build. Smart Grid, IGBSG 2014*, 2014.
- [7] M. R. Cosetin, P. C. V Luz, M. F. Da Silva, F. Bisogno, J. M. Alonso, and R. N. Do Prado, "Single-stage SEPIC-Buck converter for LED lighting with reduced storage capacitor," in *IECON Proceedings (Industrial Electronics Conference)*, 2012, pp. 4597–4603.
- [8] A. Pawellek and T. Duerbaum, "Novel Analysis of a Boost - Buck Single Stage LED - Ballast," in *PCIM Europe 2015*, 2015, no. May, pp. 19–21.
- [9] E. K. Lau, "Understanding radiation safety of high-intensity light-emitting diodes," in *Proceedings - 10th Annual IEEE Symposium on Product Compliance Engineering, ISPCE 2013*, 2013, pp. 2–4.
- [10] C. Jettanasen;, C. Pothisarn;, H. Kong, C. Jettanasen, and C. Pothisarn, "Analytical Study of Harmonics Issued from LED Lamp Driver," in *Proceedings of the International MultiConference of Engineers and Computer Scientists*, 2014, vol. II, pp. 12–15.
- [11] L. A. Fernandes, "Comparative Performance Evaluation and Assessment of Organic Light Emitting Diodes and Light Emitting Diodes," in *59th International Midwest Symposium on Circuits and Systems (MWSCAS)*, 2016, no. October, pp. 1–4.
- [12] A. Jayawardena, D. Duffy, and J. Manahan, "Impact of light on safety in industrial environments," in *Record of Conference Papers - Annual Petroleum and Chemical Industry Conference*, 2015, pp. 1–9.
- [13] F. Pareschi, G. Setti, R. Rovatti, and G. Frattini, "Practical Optimization of

- EMI Reduction in Spread Spectrum Clock Generators With Application to Switching DC/DC Converters,” *IEEE Trans. Power Electron.*, vol. 29, no. 9, pp. 4646–4657, Sep. 2014.
- [14] J. Balcells, D. Gonzalez, J. Gago, a. Santolaria, J. C. Le Bunetel, D. Magnon, and S. Brehaut, “Frequency modulation techniques for EMI reduction in SMPS,” *2005 Eur. Conf. Power Electron. Appl.*, pp. 1–8, 2005.
  - [15] W. R. Liou, H. M. Villaruza, M. L. Yeh, and P. Roblin, “A Digitally Controlled Low-EMI SPWM Generation Method for Inverter Applications,” *IEEE Trans. Ind. Informatics*, vol. 10, no. 1, pp. 73–83, 2014.
  - [16] M. Kuisma, “Variable Frequency Switching in Power Supply EMI-Control: An Overview,” *IEEE Aerosp. Electron. Syst. Mag.*, vol. 18, no. 12, pp. 18–22, 2003.
  - [17] J. H. Ahn, “Implementation of an LED tile controller for high-quality image display,” *Displays*, vol. 34, no. 1, pp. 17–26, 2013.
  - [18] A. Ndokaj and A. Di Napoli, “LED power supply and EMC compliance,” in *Energy Conference and Exhibition (ENERGYCON), 2012 IEEE International*, pp. 254–258.
  - [19] D. Sakulhirirak, V. Tarateeraseth, W. Khan-Ngern, and N. Yoothanom, “Design of high performance and low cost Line Impedance Stabilization Network for university power electronics and EMC laboratories,” *Proc. Int. Conf. Power Electron. Drive Syst.*, pp. 284–289, 2007.
  - [20] D. Nielsen, M. a. E. Andersen, and K. S. Meyer, “Preliminary investigations of piezoelectric based LED luminary,” *Proc. 2011 14th Eur. Conf. Power Electron. Appl.*, pp. 1–9, 2011.
  - [21] J. L. Kotny, T. Duquesne, and N. Idir, “Modeling and design of the EMI filter for DC-DC SiC-converter,” in *2014 International Symposium on Power Electronics, Electrical Drives, Automation and Motion, SPEEDAM 2014*, 2014, no. Cm, pp. 1195–1200.
  - [22] Y. Yang, Z. Liu, F. C. Lee, and Q. Li, “Analysis and filter design of differential mode EMI noise for gan-based interleaved MHz critical mode PFC converter,” in *2014 IEEE Energy Conversion Congress and Exposition, ECCE 2014*, 2014, pp. 4784–4789.
  - [23] L. Dong, Y. Ye, and L. He, “A Novel PWM Controller IC for LED Driver with Frequency Spread,” in *2010 Asia-Pacific Power and Energy Engineering Conference*, 2010, pp. 1–4.
  - [24] S. M. Wu and K. H. Chang, “An LED driver with active EMI mitigation scheme,” *Electron Devices Solid State Circuit, EDSSC 2012*, pp. 1–4, Dec. 2012.
  - [25] J. Niu, Y. Song, Z. Li, W. A. Halang, D. With, and T. H. E. C. Pwm, “Reducing EMI in Half-Bridge Resonant LED Drivers with Chaos-based PWM,” in *Proc. of the 2013 International Symposium on Electromagnetic Compatibility (EMC Europe 2013)*, 2013, pp. 637–640.
  - [26] N. Mohan and M. Barai, “Digital control of zero voltage switching buck converter using PIC microcontroller,” in *India International Conference on Power Electronics, IICPE*, 2012.
  - [27] L. Dung and A. Pemfc, “A Digital Boost Converter for Fuel Cell Current

- Regulation in Hybrid Power Systems,” in *Vehicle Power and Propulsion Conference (VPPC)*, 2016, pp. 0–4.
- [28] M. Kermadi, E. M. Berkouk, and A. Benachour, “Design of Discrete PI-based Current Controller for Reversible Buck Boost Converter. Digital Implementation using Arduino Due board,” in *Modelling, Identification and Control (ICMIC), 2016 8th International Conference*, 2016, pp. 863–866.
- [29] A. B. Caberos, S. Huang, X. D. G. Gumera, and W. Liou, “Design and Implementation of Hybrid Controller for AC–DC Power Factor Correction Converter,” in *2nd Annual Southern Power Electronics Conference (SPEC)*, 2016, pp. 1–5.
- [30] F. Wang and D. Boroyevich, “Model conducted EMI emission of switching modules for converter system EMI characterization and prediction,” *Conf. Rec. 2004 IEEE Ind. Appl. Conf. 2004. 39th IAS Annu. Meet.*, vol. 3, pp. 1817–1823, 2004.
- [31] Z. Emami, H. Farzanefard, and S. R. Motahari, “Precise prediction of conducted EMI in PWM flyback converters,” *Proc. - 2010 18th Iran. Conf. Electr. Eng. ICEE 2010*, vol. 2, no. L, pp. 765–771, 2010.
- [32] M. Kuisma, “Minimizing Conducted RF-Emissions in Switch Mode Power Supplies using Spread-Spectrum Techniques,” Lappeenranta University of Technology, 2004.
- [33] J.-H. Ahn, “Implementation of an LED tile controller for high-quality image display,” *Displays*, vol. 34, no. 1, pp. 17–26, Jan. 2013.
- [34] L. Svilainis, “LED brightness control for video display application,” *Displays*, vol. 29, no. 5, pp. 506–511, 2008.
- [35] J. Zheng, Z. Han, and S. Luo, “System level design of a LED lighting driver based on switching power supply,” *2009 Asia Pacific Conf. Postgrad. Res. Microelectron. Electron.*, pp. 309–312, Nov. 2009.
- [36] S. Winder, *Power Supplies for LED Drivers*, vol. 53, no. 9. Newnes, 2013.
- [37] H. W. Ott, *Electromagnetic Compatibility Engineering*. Hoboken, New Jersey: John Wiley & Sons, Inc., 2009.
- [38] Aero Safety & Maintenance, “Safety Board Calls For Fuel Tank Safety,” *Aero Safety & Maintenance*, 2017. .
- [39] European Market Surveillance Authorities, “Report to the EMC Working Party by the EMC Administrative Co-operation Group Joint Cross-Border EMC Market Surveillance Campaign Carried Out in 2004 / 05 By European Market Surveillance Authorities,” 2006.
- [40] European Market Surveillance Authorities, “Report on the Joint Cross-Border EMC Market Surveillance Campaign on domestic power tools , carried out by the European Market Surveillance Authorities in 2007 / 08,” 2008.
- [41] A. A. RADIO, “Lumatek Conducted Emissions Test Report-Electronic Ballast,” 2014.
- [42] M. H. Pong, “Status of electromagnetic compatibility research in power electronics,” in *Proceedings IPEMC 2000. Third International Power Electronics and Motion Control Conference*, 2000, vol. 1, no. 1, pp. 46–57.

- [43] K. Mainali and R. Oruganti, "Conducted EMI mitigation techniques for switch-mode power converters: A survey," *IEEE Trans. Power Electron.*, vol. 25, no. 9, pp. 2344–2356, 2010.
- [44] M. Y. Hariyawan, R. Hidayat, and E. Firmansyah, "Switch Control Scheme to Mitigate Conducted Electromagnetic Interference Emission in Light Emitting Diode Driver," *Adv. Sci. Lett.*, vol. 21, no. 12, pp. 3261–3265, 2015.
- [45] D. Hamza, M. Sawan, and P. K. Jain, "Suppression of common-mode input electromagnetic interference noise in DC–DC converters using the active filtering method," *IET Power Electron.*, vol. 4, no. 7, p. 776, 2011.
- [46] Y. Yang, X. Chang, W. Chen, and X. Yang, "Design of a differential mode active EMI filter based on conducted emission analysis used in DC/DC converter," in *31th URSI General Assembly and Scientific Symposium, URSI GASS 2014*, 2014, no. 28, pp. 2–5.
- [47] W. Xin, F. N. K. Poon, P. Road, H. Kong, N. K. Poon, C. M. Lee, and M. H. Pong, "A study of common mode noise in switching power supply from a current balancing viewpoint," *Proc. IEEE 1999 Int. Conf. Power Electron. Drive Syst. PEDS'99 (Cat. No.99TH8475)*, no. July, pp. 621–625 vol.2, 1999.
- [48] C. Wang, M. Xu, F. C. Lee, and B. Lu, "EMI study for the interleaved multi-channel PFC," in *PESC Record - IEEE Annual Power Electronics Specialists Conference*, 2007, pp. 1336–1342.
- [49] M. T. Zhang, F. C. Lee, J. Roudet, and E. Clavel, "Conducted EMI analysis of a boost PFC circuit," in *Proceedings of APEC 97 - Applied Power Electronics Conference*, 1997, vol. 1, pp. 223–229.
- [50] M. Khan, P. Magne, B. Bilgin, and S. Wirasingha, "Laminated Busbar Design Criteria in Power Converters for Electrified Powertrain Applications," *2014 IEEE Transp. Electrification Conf. Expo*, pp. 1–6, 2014.
- [51] J. P. Hong and G. W. Moon, "A digitally controlled soft valley change technique for a flyback converter," *IEEE Trans. Ind. Electron.*, vol. 62, no. 2, pp. 966–971, 2015.
- [52] H. Li, Z. Li, W. a. Halang, and W. K. S. Tang, "A chaotic soft switching PWM Boost converter for EMI reduction," *IEEE Int. Symp. Ind. Electron.*, pp. 341–346, 2008.
- [53] M. Muntasir Ul Alam, W. Eberle, and F. Musavi, "A hybrid resonant bridgeless AC-DC power factor correction converter for off-road and neighborhood electric vehicle battery charging," *Appl. Power Electron. Conf. Expo. (APEC), 2014 Twenty-Ninth Annu. IEEE*, pp. 1641–1647, 2014.
- [54] S. Mohseni and A. Roomizadeh, "Study on periodic and non periodic frequency modulation techniques for EMI suppression in SMPS," in *2011 2nd Power Electronics, Drive Systems and Technologies Conference, PEDSTC 2011*, 2011, no. 3, pp. 615–619.
- [55] C. Jin, M. T. Tan, and K. Y. See, "Filterless class-D amplifier with pseudorandomized carrier frequency modulation for EMI reduction," *IEEE Trans. Electromagn. Compat.*, vol. 55, no. 1, pp. 74–80, 2013.
- [56] S. Ho and H. Huang, "A Wideband Programmable Spread-Spectrum Clock Generator," *2005 IEEE Asian Solid-State Circuits Conf.*, pp. 521–524, Nov.

- 2005.
- [57] S. Johnson and R. Zane, "Custom spectral shaping for EMI reduction in high-frequency inverters and ballasts," *IEEE Trans. Power Electron.*, vol. 20, no. 6, pp. 1499–1505, 2005.
  - [58] C. L. Hung, K. H. Cheng, Y. C. Lin, B. Q. Jiang, C. H. Fan, and C. Y. Chang, "A 0.06-psRMS SSC-Induced Jitter,  $\Delta\Sigma$ -Dithering-Free, 6-GHz Spread-Spectrum Clock Generator for Serial-ATA Generation," in *European Solid-State Circuits Conference*, 2011, pp. 447–450.
  - [59] K. B. Hardin, J. T. Fessler, and D. R. Bush, "Spread spectrum clock generation for the reduction of radiated emissions," in *Electromagnetic Compatibility, 1994. Symposium Record. Compatibility in the Loop., IEEE International Symposium on*, pp. 227–231.
  - [60] Y. K. Park, J. H. Lim, J. K. Wee, and I. Song, "Spectrum analysis of switched-capacitor mode DPWM generator with spread-spectrum clocking circuit," *Asia-Pacific Symp. Electromagn. Compat. APEMC 2012 - Proc.*, pp. 221–224, 2012.
  - [61] H. Guo, H. Wu, B. Zhang, and Z. Li, "A novel spread-spectrum clock generator for suppressing conducted EMI in switching power supply," *Microelectronics J.*, vol. 41, no. 2–3, pp. 93–98, Feb. 2010.
  - [62] D. Stepins, "Conducted EMI of Switching Frequency Modulated Boost Converter," *Electr. Control Commun. Eng.*, vol. 3, no. 1, pp. 12–18, 2013.
  - [63] H. Li, Z. Li, B. Zhang, F. Wang, N. Tan, and W. a. Halang, "Design of analogue chaotic PWM for EMI suppression," *IEEE Trans. Electromagn. Compat.*, vol. 52, no. 4, pp. 1001–1007, 2010.
  - [64] L. Premalatha, T. A. Raghavendiran, and C. Ravichandran, "Experimental study on conducted EMI mitigation in SMPS using a novel spread spectrum technique," *J. Power Electron.*, vol. 13, no. 4, pp. 619–625, 2013.
  - [65] S. Winder, *Power Supplies for LED Driving*. 2011.
  - [66] D. G. Lamar, J. Sebastian, M. Arias, and M. M. Hernando, "A low-cost AC-DC high-brightness LED driver with power factor correction based on standard peak-current mode integrated controllers," *2010 IEEE Energy Convers. Congr. Expo. ECCE 2010 - Proc.*, pp. 463–470, 2010.
  - [67] Y. Xu, W. Lin, Y. Xu, and Y. Shao, "Inductor optimize design for BCM BUCK-PFC in LED driver," in *Electric Information and Control Engineering (ICEICE), 2011 International Conference on*, 2011, pp. 2264–2267.
  - [68] R. L. Lin, Y. C. Chang, and C. C. Lee, "Optimal design of LED array for single-loop ccm buck-boost LED driver," *IEEE Trans. Ind. Appl.*, vol. 49, no. 2, pp. 761–768, 2013.
  - [69] P. Athalye, M. Harris, and G. Negley, "A two-stage LED driver for high-performance high-voltage LED fixtures," *Appl. Power Electron. ...*, pp. 2385–2391, 2012.
  - [70] S.-M. W.; K.-H. Chang, "An LED driver with active EMI mitigation scheme," in *Electron Devices and Solid State Circuit (EDSSC)*, 2012, pp. 1–4.
  - [71] M. R. Cosetin, P. C. V Luz, M. F. da Silva, F. Bisogno, J. M. Alonso, and R.

- N. do Prado, "Long-lifetime SEPIC-buck integrated converter for LED lighting application," in *Industry Applications (INDUSCON), 2012 10th IEEE/IAS International Conference on*, pp. 1–7.
- [72] M. Arias, D. G. Lamar, F. F. Linera, D. Balocco, A. Aguisa Diallo, and J. Sebastián, "Design of a soft-switching asymmetrical half-bridge converter as second stage of an LED driver for street lighting application," *IEEE Trans. Power Electron.*, vol. 27, no. 3, pp. 1608–1621, 2012.
- [73] M. R. Cosetin, P. C. V Luz, E. A. Bitencourt, M. F. Silva, F. Bisogno, J. M. Alonso, R. N. Prado, O. F. Santa, M. Ufsm, U. D. E. Oviedo, D. Tecnología, A. Roraima, U. Bairro, and S. Maria, "Off-line Single-Stage SEPIC-Buck Converter for Dimmable LED Lighting with Reduced Storage Capacitor," in *Power Electronics and Applications (EPE), 2013 15th European Conference*, 2013, pp. 1–10.
- [74] M. R. Cosetin, P. C. V Luz, E. A. Bitencourt, M. F. da Silva, F. Bisogno, J. M. Alonso, and R. N. do Prado, "Off-line single-stage SEPIC-Buck converter for dimmable LED lighting with reduced storage capacitor," in *Power Electronics and Applications (EPE), 2013 15th European Conference on*, pp. 1–10.
- [75] International Electrotechnical Commission, "International Committee on Radio Interference." pp. 1–20, 2010.
- [76] J Klinger, "EMC and Regulatory Compliance," *Radio interference from LED lighting*, 2011. [Online]. Available: <http://www.emcrules.com/2011/07/radio-interference-from-led-lighting.html>. [Accessed: 22-Jan-2017].
- [77] D. Digital, E. Cable, L. Surges, C. Your, and L. Reflections, "LED Lighting Causes Interference," *Compliance Magazine*, pp. 1–6, 2014.
- [78] R. Maybury, "Problems with LED bulbs and DAB radio," *The Telegraph*, 2014. [Online]. Available: <http://www.telegraph.co.uk/technology/advice/11312589/Problems-with/>. [Accessed: 22-Jan-2017].
- [79] M. A. McHenry, D. Roberson, and R. J. Matheson, "Electronic Noise Is Drowning Out the Internet of Things," *IEEE Spectrum*, 2015. .
- [80] A. Karvonen and T. Thiringer, "Simulating the EMI characteristics of flyback DC/DC converters," in *INTELEC, International Telecommunications Energy Conference (Proceedings)*, 2011.
- [81] A. Esmaeli, Z. Ke, and S. Li, "A Systematic Approach to the Conducted EMI Suppression in Plasma Cutting Power Supply," in *9th International Multitopic Conference, IEEE INMIC 2005*, 2005, pp. 1–6.
- [82] Y. Zhou, Y. Zhu, Q. Song, Z. Jin, D. Yang, and X. Yu, "Prediction and reduction of electromagnetic conducted emission in active clamp forward converter," *IEEE Int. Symp. Electromagn. Compat.*, pp. 729–733, 2011.
- [83] K. Mainali and R. Oruganti, "Simple Analytical Models to Predict Conducted EMI Noise in a Power Electronic Converter," in *IECON 2007 - 33rd Annual Conference of the IEEE Industrial Electronics Society*, 2007, vol. 0, pp. 1930–1936.
- [84] G. Spadacini, D. Bellan, S. A. Pignari, R. Grossi, and F. Marliani,

- “Prediction of conducted emissions of DC/DC converters for space applications,” *2010 Asia-Pacific Symp. Electromagn. Compat. APEMC 2010*, pp. 798–801, 2010.
- [85] S. Wesling and S. Dickmann, “Prediction of Conducted Emissions produced by a DC-DC-Converter using Component Parasitics and Partial Inductances,” *2013 Int. Symp. Electromagn. Compat. (EMC Eur.)*, pp. 627–631, 2013.
- [86] F. C. Lee and W. G. Odendaal, “Modeling and characterization of a 1KW CCM PFC converter for conducted EMI prediction,” in *Nineteenth Annual IEEE Applied Power Electronics Conference and Exposition, 2004. APEC '04.*, 2004, vol. 2, no. C, pp. 763–769.
- [87] T. Wuest, D. Weimer, C. Irgens, and K.-D. Thoben, “Machine learning in manufacturing: advantages, challenges, and applications,” *Prod. Manuf. Res.*, vol. 4, no. 1, pp. 23–45, 2016.
- [88] X. Li and Z. Deng, “A Machine Learning Approach to Predict Turning Points for Chaotic Financial Time Series,” in *19th IEEE International Conference on Tools with Artificial Intelligence (ICTAI 2007)*, 2007, pp. 331–335.
- [89] K. Li and Y.-S. Liu, “Fuzzy case-based reasoning: weather prediction,” in *First International Machine Learning and Cybernetics*, 2002, vol. 1, pp. 107–110.
- [90] S. Aiguo and Z. Bo, “K-Nearest Neighbor LS-SVM Method for Multi-step Prediction of Chaotic Time Series,” in *Symposium on Electrical & Electronics Engineering (EEESYM) K-Nearest*, 2012, pp. 407–409.
- [91] L. Faes, K. H. Chon, and G. Nollo, “A method for the time-varying nonlinear prediction of complex nonstationary biomedical signals,” *IEEE Trans. Biomed. Eng.*, vol. 56, no. 2, pp. 205–209, 2009.
- [92] A. Rafael, S. Parmezan, and G. E. A. P. A. Batista, “A Study of the Use of Complexity Measures in the Similarity Search Process Adopted by k NN Algorithm for Time Series Prediction,” *14th Int. Conf. Mach. Learn. Appl. (IEEE ICMLA '15)*, 2015.
- [93] T. Vialar, *Complex and Chaotic Nonlinear Dynamics-Advances in Economics and Finance*. 2009.
- [94] W. L. Woon, A. El-hag, and M. Harbaji, “Machine learning techniques for robust classification of partial discharges in oil – paper insulation systems,” *IET Sci. Meas. Technol.*, vol. 10, no. 221–227, pp. 1–7, 2015.
- [95] J. C. Sprott, “Simplifications of the Lorenz attractor.,” *Nonlinear Dynamics. Psychol. Life Sci.*, vol. 13, no. 3, pp. 271–278, 2009.
- [96] S. K. Bhowmick, “How to generate chaotic pulse?,” *Int. Journal Nonlinear Sci.*, vol. 17, no. 1, pp. 67–70, 2014.
- [97] S. Jog, N. Chaturvedi, and S. Chitnis, “Electromagnetic Compatibility of Energy Efficient EMI Standards,” in *International Conference on Energy Systems and Applications (ICESA)*, 2015, no. Icesa, pp. 700–705.
- [98] J. Mon, D. Gonzalez, J. Gago, J. Balcells, a. Santolaria, and L. Ferrer, “Side effects evaluation of switching frequency modulation in power converters,” *IECON Proc. (Industrial Electron. Conf.)*, no. 2, pp. 1643–1648, 2006.
- [99] M. Merhy, C. Morel, E. Chauveau, M. Machmoum, and C. Morel, “Reducing

- the Spectral Emissions of PFC Converters by Anticontrol of Chaos,” *Int. J. Power Electron. Drive Syst.*, vol. 3, no. 2, pp. 129–146, 2013.
- [100] F. Pareschi, G. Setti, R. Rovatti, and G. Frattini, “Practical Optimization of EMI Reduction in Spread Spectrum Clock Generators With Application to Switching DC/DC Converters,” *Power Electron. IEEE Trans.*, vol. 29, no. 9, pp. 4646–4657, 2014.
- [101] Z. Cao and Y. Zhang, “Variable Frequency Modulation for EMI Suppressing in Power Converter,” *Energy Power Eng.*, vol. 5, no. 4, pp. 1147–1152, 2013.
- [102] T. Nadu, “Generation of Randomized Firing Signals using FPGA to Hold Back EMI in Buck Converter under Various Load Conditions,” no. 1, pp. 723–728, 2014.
- [103] J. Calusdian and X. Yun, “Microcontroller Generates Chaotic Lorenz Signals,” *Electronic Design*, 2014. [Online]. Available: <http://www.electronicdesign.com/analog/microcontroller-generates-chaotic-lorenz-signals>. [Accessed: 15-Dec-2017].