



UNIVERSITAS  
GADJAH MADA

ANALISIS SIFAT MEKANIS NANOCOMPOSITES RAMI YANG DIMANUFAKTUR DENGAN METODE  
VACUUM ASSISTED RESIN  
TRANSFER MOLDING

GERY PRIZLANTO, Ir. Heru Santoso B.R., M.Eng., Ph.D

Universitas Gadjah Mada, 2017 | Diunduh dari <http://etd.repository.ugm.ac.id/>

## DAFTAR PUSTAKA

Abdul Khalil, HPS (1999): *Acetylated plant fibre reinforced composites, PhD Thesis, School of Agricultural and Forest Sciences*, University of Wales, Bangor, Gwynedd, United Kingdom.

Alemdar, A., & Sain, M. (2008). *Isolation and characterization of nanofibers from agricultural residues – Wheat straw and soy hulls*. *Bioresource Technology*, 99, 1664–2167.

Berglund, L., 2005. *Cellulose-Based Nanocomposites*. In: A.K.M. Mohanty, M.; Drzal, L.(Editor), Natural fibers, biopolymers, and biocomposites. Taylor & Francis, pp. 807-832.

Callister, W.D., 2003, *Material Science and Engineering An Introduction*, John Wiley and Sons, Inc.

Chakraborty, A., Sain, M., & Kortschot, M. (2005). *Cellulose microfibrils: A novel method of preparation using high shear refining and cryocrushing*. *Holzforschung*, 59, 102–107.

Chauhan, V. S., & Chakrabarti, S. K. (2012). *Use of nanotechnology for high performance cellulosic and papermaking products*. *Cellulose Chemistry and Technology*, 46(5–6), 389–400.



Chen, P., Yu, H., Liu, Y., Chen, W., Wang, X., & Ouyang, M. (2013). *Concentration effects on the isolation and dynamic rheological behavior of cellulose nanofibers via ultrasonic processing*. Cellulose, 20, 149–157.

Cheng, Q., Wang, S., & Rials, T. G. (2009). *Poly(vinyl alcohol) nanocomposites reinforced with cellulose fibrils isolated by high intensity ultrasonication*. Composites: Part A, 40, 218–224.

Corrêa, A. C., Teixeira, E. M., Pessan, L. A., & Mattoso, L. H. C. (2010). *Cellulose nanofibers from curaua fibers*. Cellulose, 17, 1183–1192.

Dewi T. K, Dandy, Akbar W.2010. *Pengaruh Konsentrasi NaOH, Temperatur Pemasakan, dan Lama Pemasakan pada Pembuatan Pulp dari Batang Rami dengan Proses Soda*. Jurnal Teknik Kimia. 17, 68-74.

Dufresne, A., Dupeyre, D., & Vignon, M. R. (2000). *Cellulose microfibrils from potato tuber cells: Processing and characterization of starch-cellulose microfibril composites*. Journal of Applied Polymer Science, 76, 2080–2092.

Eichhorn, S. J., Dufresne, A., Aranguren, M., Marcovich, N. E., Capadona, J. R., Rowan, S.J., et al. (2010). *Review: Current international research into cellulose nanofibres and nanocomposites*. Materials Science, 45, 1–33.

Elias J. Rigas, Thomas J. Mulkern, Shawn M. Walsh, and Steven P. Nguyen, 2001. *Effects of Processing Conditions on Vacuum Assisted Resin Transfer Molding Process (VARTM)*. University of Delaware.



Ferrer, A., Filpponen, I., Rodriguez, A., Laine, J., & Rojas, O. J. (2012). *Valorization of residual Empty Palm Fruit Bunch Fibers (EPFBF) by microfluidization: Production of nanofibrillated cellulose and EPFBF nanopaper*. Bioresource Technology, 125, 249–255.

Frone, A. N., Panaitescu, D. M., & Donescu, D. (2011). *Some aspects concerning the isolation of cellulose micro- and nano-fibers*. U.P.B. Science Bulletin, Series B, 73(2), 133–152.

George, J., Sreekala, M.S. and Thomas, S., 2001. A review on interface modification and characterization of natural fiber reinforced plastic composites. *Polymer Engineering and Science*, 41(9): 1471-1485.

Gibson, R.F., 1994, *Principles of Composites Material Mechanics*, International Edition, McGraw-Hill Book Company, New York, USA Harris.

Goda, K., Sreekala, M.S., Gomes, A., Kaji, T., Ohgi, J., 2005, *Improvement Of Plant Based Natural Fibers For Toughening Green Composites—Effect Of Load Application During Mercerization Of Ramie Fibers*, Department of Mechanical Engineering, Yamaguchi University, Tokiwadai, Japan.7, 1-7.

Johnson, DJ (1979): *High – Temperature stable and high – performance fibres, Applied Fibre Science*, Vol. 3, Happey, F (ed.), Academic press, Chapter 3.

Kamel, S. (2007). *Nanotechnology and its applications in lignocellulosic composites, a mini review*. Express Polymer Letters, 1, 546–575.

Lima, M. M. S., & Borsali, R. (2004). *Rodlike cellulose microcrystals: Structure, properties, and applications*. Macromolecular Rapid Communications, 25, 771–787.



Mallick, P.K., 2007, *Fiber-reinforced Composites*, 3 rd Ed., CRC Press, USA.

Maryanti B., Sonief A.A., Wahyudi S. (2011). *Pengaruh alkalisasi komposit serat kelapa/polyester terhadap kekuatan tarik*. Jurnal Rekayasa Mesin.2, 123-129.

Moncrieff, RW (1975): *Cellulose acetate, man made fibres*, Newnes-Butterworth, London, 232-262.

Nakagaito, A. N., & Yano, H. (2004). *The effect of morphological changes from pulp fiber towards nano-scale fibrillated cellulose on the mechanical properties of high-strength plant fiber based composites*. Applied Physics A – Material Science Process, 78, 547–552.

Panthapulakkal, S., & Sain, M. (2012). *Preparation and characterization of cellulose nanofibril films from wood fibre and their thermoplastic polycarbonate composites*. International Journal of Polymer Science, 1–6.

Prasanth R., Shubha N., Hoon Hng H. , Srinivasan M. 2013. *Effect of nano-clay on ionic conductivity and electrochemical properties of poly(vinylidene fluoride) based nanocomposite porous polymer membranes and their application as polymer electrolyte in lithium ion batteries*. Nanyang Technological University. Singapore. 17, 69-74.

Rivero R.E., Molina M.A., Rivarola C.R., Barbero C.A. 2014. *Pressure and microwave sensors/actuators based on smart hydrogel/conductive polymer nanocomposite*. Univercidad Nacional de Rio Cuarto. Argentina. 5, 76-87.



Rowell, RM, Vigo, T and Kinzig, B (eds.) (1992): Property enhancement of wood composites, in “*Composite applications - the role of matrix, fibre and interface*”, , VCH Publishers, New York

Shenouda, SG (1979): *The structure of cotton cellulose*, Applied Fibre Science, vol. 3, Happey, F (ed.), Academic press, 275 – 309.

Siro, I., & Plackett, D. (2010). *Microfibrillated cellulose and new nanocomposite materials: A review*. Cellulose, 17, 459–494.

Siqueira, G., Bras, J., & Dufresne, A. (2009). Cellulose whiskers versus microfibrils: *Influence of the nature of the nanoparticle and its surface functionalization on the thermal and mechanical properties of nanocomposites*. Biomacromolecules, 10, 425–432.

Skramstad, Jon D. 2000., “*Evaluation of Hand Lay-up and Resin Transfer Molding in Composite Wind Turbine Blade Manufacturing*”, Masters Thesis, Mechanical Engineering Department, Montana State University.

Sreekala, MS; Kumaran, MG and Thomas, S (1997): *Oil palm fibres: Morphology, Chemical composition, surface modification, and mechanical properties*, Journal of Applied Polymer Science, Vol. 66, 821 – 835.

Teixeira, E. M., Corrêa, A. C., Manzoli, A., Leite, F. L., Oliveira, C. R., & Mattoso, L. H.C. (2010). *Cellulose nanofibers from white and naturally colored cotton fibers*. Cellulose, 17, 595–606.



Tripathi B.P, Shahi V.K .2011. *Organic-inorganic nanocomposite polymer electrolyte membranes for fuel cell applications.* Central Salt and Marine Chemicals Research Institute, Gujarat. India.

Wen L., Wen-guang L., Chao R.(2006). *Effect of volume fraction of ramie cloth on physical and mechanical properties of ramie cloth/UP resin composite.* Transactions of Nonferrous Metal Society of China. 16, 1-4.

Yano H., Uetani K. 2011. *Nanofibrillation of Wood Pulp Using High Speed Blender.* Kyoto University. Japan.