

## DAFTAR PUSTAKA

- [1] Dewan Energi Nasional, 2015, BPPT Indonesia Energi Outlook.
- [2] Y. Daryanto (2007), *Kajian Potensi Angin untuk Pembangkit Listrik Tenaga Bayu*, BALAI PPTAGG-UPT-LAGG, Yogyakarta.
- [3] Jarass (1980), *Strom aus Wind – Integration einer regenerativen Energie Quelle*, Springer-Verlag, Berlin.
- [4] BTM Consults ApS (2005), *International Wind Energy Development World Market Update 2004 Forecast 2005-2009*, Press Release March 31, 2005.
- [5] Wahyu, D., Purwanto, 2011. *Analisa Variasi Geometri Terhadap Kinerja Difuser pada Difuser Augmented Wind Turbine*. ITS. Surabaya.
- [6] Y. Ohya, T. Karasudani, A. Sakurai, M. Inoue, N. Miura, Part 2 – Development of high performance wind turbine system by wind lens effect (locally concentrated wind energy), Proceedings of the 24<sup>th</sup> Symposium on Wind Energy Utilization, Tokyo, 2002, pp. 165 – 168 (in Japanese).
- [7] Renewable Electricity Futures Study, Volume 2: Renewable Electricity Generation and Storage Technologies.
- [8] “Persamaan Pembentuk Aliran (Governing Equations)”.
- [9] Yuji Ohya, Takahashi, K., Akira S., and Masashiro, I. Development of a shrouded wind turbine with a flanged diffuser. *Journal of Wind Engineering and Industrial Aerodynamics*, 96, pp, 524-539, 2008.
- [10] Tito, A., Wibowo, H., Wahyuono, R. A. (2013). Studi Numerik Pengaruh Geometri dan Desain Diffuser untuk Peningkatan Kinerja DAWT (Diffuser Augmented Wind Turbine), *I4(2)*, 90–96. doi:10.9744/jtm.14.2.90-96



- [11] Grassmann, H., Bet, F., Ceschia, M., & Ganis, M. L. (2004). On the physics of partially static turbines. *Renewable Energy*, 29(4), 491–499. doi: 10.1016/j.renene.2003.07.008
- [12] Maria, A., & Ferreira, B. (2013). Numerical Study of Flow Around Diffusers with Different Geometry Using CFD Applied to Hydrokinetics Turbines, (Cobem), 1033–1040.
- [13] Kannan, T. S., Mutasher, S. A., & Lau, Y. H. K. (2013). Design and Flow Velocity Simulation of Diffuser Augmented Wind Turbine Using CFD, 8(4), 372–384.
- [14] A. Grant, R. K.W. Dannecker, “Investigations of a building-integrated shrouded wind turbine module”. *Wind Energy*. Vol. 5, pp. 53-71, 2002.
- [15] S.Y. Hua, J.H. Cheng, “Innovatory designs for shrouded wind turbines”. *Renewable Energy*. Vol 33, pp. 1491 – 1498, 2007.
- [16] Ibrahim, Herman D. *Mempercepat Implementasi Pengembangan Energi Terbarukan untuk Ketenagalistrikan*. DESDM. Jakarta, 19 Mei 2008.
- [17] Wyrтки, K., 1987: *Indonesian through flow and the associated pressure gradient*. *J. Geophys. Res.-Oceans*, 92 (C12), 12941-12946.
- [18] Baldwin, S. (2006). Carbon footprint of electricity generation. *United Kingdom Parliamentary Office of Science and Technology*. Retrieved from [http://www.geni.org/globalenergy/library/technical-articles/carbon-capture/parliamentary-office-of-science-and-technology/carbon-footprint-of-electricity-generation/file\\_9270.pdf](http://www.geni.org/globalenergy/library/technical-articles/carbon-capture/parliamentary-office-of-science-and-technology/carbon-footprint-of-electricity-generation/file_9270.pdf)
- [19] Kusdiana. 2008. *Kondisi Riil Kebutuhan Energi di Indonesia dan Sumber Energi Alternatif Terbarukan*. Dirjen Listrik dan Pemanfaatan Energi DESDM. Bogor.



- [20] Van Bussel GJW. The Science of Making More Torque from Wind: Diffuser Experiments and Theory Revisited. *Journal of Physics: Conference Series*, IOP Publishing 2007;75:1-12. Available from: <http://iopscience.iop.org/1742-6596/75/1/012010>.
- [21] Hakim, L., 2012. Universitas Indonesia. *Analisa pemakaian selubung (shroud) dengan penambahan flanged pada turbin angin di daerah pemukiman*. Jakarta
- [22] Purwanto, D. W. (2010). *Interior lengkung difuser untuk peningkatan performansi Diffuser-Augmented Wind Turbine (DAWT)*. Prosiding Seminar Nasional Energi Terbarukan Indonesia I, 18–19 Desember 2010. Purwokerto.
- [23] Phillips, D.G.; Flay, R.G.J.; and Nash, T.A. (1999) Aerodynamic analysis and monitoring of the Vortec 7 diffuser augmented wind turbine. *Transactions of the Institution of Professional Engineers New Zealand*, 26(1), 13-19.
- [24] Matsushima, T.; Takagi, S.; and Muroyama, S. (2006). Characteristics of a highly efficient propeller types small wind turbine with a diffuser. *Renewable Energy*, 31(9), 1343–1354.
- [25] ANSYS Fluent User Manual by ANSYS Inc.
- [26] Elbalsohi, A. E. M., Hu, J., & Jia, R. (2014). *Simulation of Turbulent Flow in an Asymmetric Air Diffuser*. Department of Mechanical Engineering, University of Bridgeport, USA.
- [27] Manihuruk, Dedy Prima. (2008). *Analisis CFD pada Turbin Savonius Tipe U Overlap*. Departemen Teknik Nuklir dan Teknik Fisika, Universitas Gadjah Mada, Yogyakarta.



- [28] Roshan, S. Z., Alimirzazadeh, S., & Rad, M. (2015). Journal of Wind Engineering RANS simulations of the stepped duct effect on the performance of ducted wind turbine. *Jnl. of Wind Engineering and Industrial Aerodynamics*, 145, 270–279.  
<http://doi.org/10.1016/j.jweia.2015.07.010>
- [29] Andre Bakker. (2006). Lecture 10 - Turbulence Models Applied Computational Fluid Dynamics. *Lecture Notes*, (2002), 1–47.
- [30] Tuakia, Firman. *Dasar-dasar CFD Menggunakan FLUENT*. Penerbit Informatika, Bandung. 2008.
- [31] Abe, K. I., & Ohya, Y. (2004). An investigation of flow fields around flanged diffusers using CFD. *Journal of Wind Engineering and Industrial Aerodynamics*, 92(3-4), 315–330.  
<http://doi.org/10.1016/j.jweia.2003.12.003>
- [32] Canonsburg, T. D. (2009). Meshing Help, 15317(November), 724–746.
- [33] Mansour, K., & Meskinkhoda, P. (2014). Journal of Wind Engineering Computational analysis of flow fields around flanged diffusers, 124, 109–120. <http://doi.org/10.1016/j.jweia.2013.10.012>
- [34] BMKG Indonesia. Diakses dari [http://bmkg.go.id/BMKG\\_Pusat/Informasi\\_Cuaca](http://bmkg.go.id/BMKG_Pusat/Informasi_Cuaca), 1 Juli 2016.
- [35] Kutut Suryopratomo. “Ketersediaan Angin”. Kuliah *Rekayasa Energi Bayu*, Departemen Teknik Nuklir dan Teknik Fisika, Fakultas Teknik Universitas Gadjah Mada, Yogyakarta, 2015.
- [36] Alfian, Muhammad. (2011). *Uji Eksperimental Pengaruh Jumlah Sudu dan Variasi Kecepatan Angin Terhadap Daya dan Putaran Turbin Angin Savonius dengan Luas Sapuan Rotor 0,90 m<sup>2</sup>*. Departemen Teknik Mesin, Fakultas Teknik, Universitas Sumatera Utara, Medan.



- [37] WHyPGen – BPPT. Diakses dari [www.whypgen-bppt.com](http://www.whypgen-bppt.com), 24 Juni 2016.
- [38] Wind Power Program. Diakses dari [www.wind-power-program.com](http://www.wind-power-program.com), 25 Juni 2016.
- [39] Kalmikov, A., & Dykes, K. (2010). Wind Power Fundamentals. *MIT Wind Energy Group & Renewable Energy Projects in Action*, 42.
- [40] Pikatan, Sugata. (1999). Konversi Energi Angin: Departemen MIPA, Universitas Surabaya, Surabaya.