

## DAFTAR PUSTAKA

- [1] J. Kang, F. Yan, P. Zhang, and C. Du, "Comparison of comprehensive properties of Ni-MH (nickel-metal hydride) and Li-ion (lithium-ion) batteries in terms of energy efficiency," *Energy*, vol. 70, no. 2014, pp. 618–625, 2014.
- [2] Y. Çadirci and Y. Özkazanç, "Microcontroller-based on-line state-of-charge estimator for sealed lead-acid batteries," *J. Power Sources*, vol. 129, no. 2, pp. 330–342, 2004.
- [3] K. S. Ng, C.-S. Moo, Y.-P. Chen, and Y.-C. Hsieh, "Enhanced coulomb counting method for estimating state-of-charge and state-of-health of lithium-ion batteries," *Appl. Energy*, vol. 86, no. 9, pp. 1506–1511, 2009.
- [4] M. Mastali, J. Vazquez-Arenas, R. Fraser, M. Fowler, S. Afshar, and M. Stevens, "Battery state of the charge estimation using Kalman filtering," *J. Power Sources*, vol. 239, no. 2013, pp. 294–307, 2013.
- [5] B. Pattipati, B. Balasingam, G. V. Avvari, K. R. Pattipati, and Y. Bar-Shalom, "Open circuit voltage characterization of lithium-ion batteries," *J. Power Sources*, vol. 269, no. 2014, pp. 317–333, 2014.
- [6] Y. Xing, W. He, M. Pecht, and K. L. Tsui, "State of charge estimation of lithium-ion batteries using the open-circuit voltage at various ambient temperatures," *Appl. Energy*, vol. 113, no. 2014, pp. 106–115, 2014.
- [7] S. Lee, J. Kim, J. Lee, and B. H. Cho, "State-of-charge and capacity estimation of lithium-ion battery using a new open-circuit voltage versus state-of-charge," *J. Power Sources*, vol. 185, no. 2, pp. 1367–1373, 2008.
- [8] K. T. Chau, K. C. Wu, and C. C. Chan, "A new battery capacity indicator for lithium-ion battery powered electric vehicles using adaptive neuro-fuzzy inference system," *Energy Convers. Manag.*, vol. 45, no. 11–12, pp. 1681–1692, 2004.
- [9] W. X. Shen, "State of available capacity estimation for lead-acid batteries in electric vehicles using neural network," *Energy Convers. Manag.*, vol. 48, no. 2007, pp. 433–442, 2007.
- [10] Y. Shen, "Adaptive online state-of-charge determination based on neuro-controller and neural network," *Energy Convers. Manag.*, vol. 51, no. 5, pp. 1093–1098, 2010.
- [11] P. Singh, C. Fennie, and D. Reisner, "Fuzzy logic modelling of state-of-charge and available capacity of nickel/metal hydride batteries," *J. Power Sources*, vol. 136, no. 2, pp. 322–333, 2004.
- [12] P. Singh, R. Vinjamuri, X. Wang, and D. Reisner, "Design and implementation of a fuzzy logic-based state-of-charge meter for Li-ion batteries used in portable defibrillators," *J. Power Sources*, vol. 162, no. 2 SPEC. ISS., pp. 829–836, 2006.
- [13] C. Burgos, D. Sáez, M. E. Orchard, and R. Cárdenas, "Fuzzy modelling for the state-of-charge estimation of lead-acid batteries," *J. Power Sources*, vol. 274, no. 2015, pp. 355–366, 2015.
- [14] J. N. Hu, J. J. Hu, H. B. Lin, X. P. Li, C. L. Jiang, X. H. Qiu, and W. S. Li, "State-

- of-charge estimation for battery management system using optimized support vector machine for regression,” *J. Power Sources*, vol. 269, pp. 682–693, 2014.
- [15] J. C. Álvarez Antón, P. J. García Nieto, F. J. de Cos Juez, F. Sánchez Lasheras, M. González Vega, and M. N. Roqueñí Gutiérrez, “Battery state-of-charge estimator using the SVM technique,” *Appl. Math. Model.*, vol. 37, no. 8, pp. 6244–6253, 2013.
- [16] T. Hansen and C.-J. Wang, “Support vector based battery state of charge estimator,” *J. Power Sources*, vol. 141, no. 2, pp. 351–358, 2005.
- [17] J. M. Mendel, R. I. John, and F. Liu, “Interval Type-2 Fuzzy Logic Systems Made Simple,” *Fuzzy Syst. IEEE Trans.*, vol. 14, no. 6, pp. 808–821, 2006.
- [18] J. M. Mendel, *Uncertain Rule-Based Fuzzy Logic System: Introduction and New Directions*. NJ, 2001.
- [19] D. Wu and J. M. Mendel, “Enhanced Karnick-Mendel Algorithms for Interval Type-2 Fuzzy Sets and Systems,” *Proc. Nafips 2007*, pp. 184–189, 2007.
- [20] J. M. Mendel, “Uncertainty Bounds and Their use in the Design of Interval Type-2 Fuzzy Logic Systems,” *IEEE Trans. Fuzzy Syst.*, vol. 10, no. 5, pp. 622–639, 2002.
- [21] C. Lynch, H. Hagrais, and V. Callaghan, “Using uncertainty bounds in the design of an embedded real-time type-2 neuro-fuzzy speed controller for marine diesel engines,” *IEEE Int. Conf. Fuzzy Syst.*, pp. 1446–1453, 2006.
- [22] K. Duran, H. Bernal, and M. Melgarejo, “Improved iterative algorithm for computing the generalized centroid of an interval type-2 fuzzy set,” *NAFIPS 2008 - 2008 Annu. Meet. North Am. Fuzzy Inf. Process. Soc.*, pp. 1–5, 2008.
- [23] D. Wu and J. M. Mendel, “Enhanced Karnik-Mendel algorithms,” *IEEE Trans. Fuzzy Syst.*, vol. 17, no. 4, pp. 923–934, 2009.
- [24] D. Wu and M. Nie, “Comparison and practical implementation of type-reduction algorithms for type-2 fuzzy sets and systems,” *2011 IEEE Int. Conf. Fuzzy Syst. (FUZZ-IEEE 2011)*, no. 6, pp. 2131–2138, 2011.
- [25] C. Y. Yeh, W. H. R. Jeng, and S. J. Lee, “An enhanced type-reduction algorithm for type-2 fuzzy sets,” *IEEE Trans. Fuzzy Syst.*, vol. 19, no. 2, pp. 227–240, 2011.
- [26] S. Sepasi, R. Ghorbani, and B. Y. Liaw, “Improved extended Kalman filter for state of charge estimation of battery pack,” *J. Power Sources*, vol. 255, no. 2014, pp. 368–376, 2014.
- [27] K. Lim, H. Ayad, V. Duong, K. Wai, P. Zhang, and S. Xue, “Fading Kalman filter-based real-time state of charge estimation in LiFePO<sub>4</sub> battery-powered electric vehicles,” *Appl. Energy*, vol. 169, no. 2016, pp. 40–48, 2016.
- [28] L. Sánchez, I. Couso, and J. C. Viera, “Online SOC estimation of Li-FePO<sub>4</sub> batteries through a new fuzzy rule-based recursive filter with feedback of the heat flow rate,” *2014 IEEE Veh. Power Propuls. Conf. VPPC 2014*, pp. 1–6, 2015.
- [29] Y.-S. Cheng, C.-M. Young, Y.-H. Liu, G.-J. Chen, and Z.-Z. Yang, “Design and implementation of Li-ion battery charger using state-of-charge estimation with fuzzy temperature control,” *Ind. Technol. (ICIT), 2015 IEEE Int. Conf.*, no. 1, pp. 2075–2079, 2015.

- [30] R. Feng, S. Zhao, and X. Lu, "On-line estimation of Dynamic State-of-Charge for lead acid battery based on fuzzy logic," *Int. Conf. Meas. Inf. Control*, no. 1, pp. 447–451, 2013.
- [31] X. Yan, Y. Yang, Q. Guo, H. Zhang, and W. Qu, "Electric vehicle battery SOC estimation based on fuzzy Kalman filter," *2013 2nd Int. Symp. Instrum. Meas. Sens. Netw. Autom.*, no. 1, pp. 863–866, 2013.
- [32] H.-T. Lin, "Fuzzy Inference System based Fuzzy Neural Networks," pp. 891–896, 2013.
- [33] H. T. Lin, T. J. Liang, S. M. Chen, and K. W. Li, "Forecasting the state-of-charge of Li-ion batteries using fuzzy inference system and fuzzy identification," *2012 IEEE Energy Convers. Congr. Expo. ECCE 2012*, pp. 3175–3181, 2012.
- [34] W. X. Shen, C. C. Chan, E. W. C. Lo, and K. T. Chau, "A new battery available capacity indicator for electric vehicles using neural network," *Energy Convers. Manag.*, vol. 43, no. 2002, pp. 817–826, 2002.
- [35] Y. Chen and D. Wang, "Studies on Centroid Type-Reduction Algorithms for Interval Type-2 Fuzzy Logic Systems," *2015 IEEE Fifth Int. Conf. Big Data Cloud Comput.*, pp. 344–349, 2015.
- [36] D. Wu, "Approaches for reducing the computational cost of interval type-2 fuzzy logic systems: Overview and comparisons," *IEEE Trans. Fuzzy Syst.*, vol. 21, no. 1, pp. 80–99, 2013.
- [37] T. Kamu, "Evolusi Perkembangan Teknologi Mobil Listrik Dunia," 2015. [Online]. Available: <http://tahukah-engkau.blogspot.com/2010/09/evolusi-perkembangan-teknologi-mobil.html>. [Accessed: 16-Apr-2016].
- [38] Wikipedia, "Battery Management System," 2015. [Online]. Available: [https://en.wikipedia.org/wiki/Battery\\_management\\_system](https://en.wikipedia.org/wiki/Battery_management_system). [Accessed: 11-Apr-2016].
- [39] Woodbank Communications Ltd, "Battery and Energy Technologies," 2005. [Online]. Available: <http://www.mpoweruk.com/bms.htm#top>. [Accessed: 12-Apr-2016].
- [40] L. Lu, X. Han, J. Li, J. Hua, and M. Ouyang, "A review on the key issues for lithium-ion battery management in electric vehicles," *Journal of Power Sources*, vol. 226, no. 2013. Elsevier B.V, pp. 272–288, 2013.
- [41] A. K. . K. S. N. J. B. G. Padhi, "Phospho-olivines as Positive Electrode Materials for Rechargeable Lithium Batteries," *J. Electrochem. Soc.*, vol. 144, no. 4, 1997.
- [42] H. ping Liu, Z. xing Wang, X. hai Li, H. jun Guo, W. jie Peng, Y. he Zhang, and Q. yang Hu, "Synthesis and electrochemical properties of olivine LiFePO<sub>4</sub> prepared by a carbothermal reduction method," *J. Power Sources*, vol. 184, no. 2, pp. 469–472, 2008.
- [43] A. Fotouhi, D. J. Auger, K. Propp, S. Longo, and M. Wild, "A review on electric vehicle battery modelling: From Lithium-ion toward Lithium–Sulphur," *Renew. Sustain. Energy Rev.*, vol. 56, no. 2016, pp. 1008–1021, 2016.
- [44] C. Y. Chun, J. Baek, G. S. Seo, B. H. Cho, J. Kim, I. K. Chang, and S. Lee, "Current sensor-less state-of-charge estimation algorithm for lithium-ion batteries

- utilizing filtered terminal voltage,” *J. Power Sources*, vol. 273, no. 2015, pp. 255–263, 2015.
- [45] Z. Chen, Y. Fu, and C. C. Mi, “State of charge estimation of lithium-ion batteries in electric drive vehicles using extended Kalman filtering,” *IEEE Trans. Veh. Technol.*, vol. 62, no. 3, pp. 1020–1030, 2013.
- [46] W.-Y. Chang, “The State of Charge Estimating Methods for Battery: A Review,” *ISRN Appl. Math.*, vol. 2013, no. 1, pp. 1–7, 2013.
- [47] Y. Zou, X. Hu, H. Ma, and S. E. Li, “Combined State of Charge and State of Health estimation over lithium-ion battery cell cycle lifespan for electric vehicles,” *J. Power Sources*, vol. 273, no. 2015, pp. 793–803, 2015.
- [48] J. Aladi and C. Garibaldi, “Type-1 or Interval Type-2 Fuzzy Logic Systems-On the Relationship of the Amount of Uncertainty and FOU Size,” in *Ima.Ac.Uk*, 2014, pp. 1–22.
- [49] Wikipedia, “Mean Square Error,” 2016. [Online]. Available: [https://en.wikipedia.org/wiki/Mean\\_squared\\_error](https://en.wikipedia.org/wiki/Mean_squared_error). [Accessed: 27-May-2016].
- [50] Wikipedia, “Root Mean Square Error,” 2016. [Online]. Available: [https://en.wikipedia.org/wiki/Root-mean-square\\_deviation](https://en.wikipedia.org/wiki/Root-mean-square_deviation). [Accessed: 27-May-2016].