

Table of Contents

COVER	i
THESIS ENDORSEMENT	ii
DECLARATION OF ACADEMIC INTEGRITY.....	iii
ACKNOWLEDGEMENT	iv
TABLE OF CONTENTS	v
LIST OF TABLES	viii
LIST OF FIGURES.....	x
ABSTRACT	xii
INTISARI.....	xiii
CHAPTER 1 INTRODUCTION	1
1.1 Introduction	1
1.2 Problem Statement	4
1.3 Hypothesis.....	4
1.4 Objective of the Study.....	4
1.5 Advantages of the Study	5
1.6 Scope of the Study	5
1.7 Originality	5
CHAPTER 2 LITERATURE REVIEW	6
2.1 Signalized Intersection.....	6
2.2 Modern Roundabout.....	8
2.3 Effects of Converting Signalized Intersection to Roundabout.....	13
2.3.1 Conflict Points.....	15
2.3.2 Sustainability Transportation	17
CHAPTER 3 THEORETICAL FRAMEWORK	19
3.1 Design Guideline.....	19
3.2 Vehicle Types, Vehicle Class and Desire Speed	27
3.3 Micro Simulation of Roundabout using VISSIM	29
3.3.1 Links and Connector	30

3.3.2 Routing Decision.....	30
3.3.3 Priority Rules	31
3.3.4 Reduced Speed Zone.....	33
3.4 Calibration and Validation in VISSIM	35
3.4.1 Calibration.....	35
3.4.2 Validation.....	36
3.5 Statistical Analysis	38
CHAPTER 4 RESEARCH METHOD.....	39
4.1 Introduction	39
4.2 Case Study Location	40
4.3 Data Collection.....	41
4.3.1. Primary Data	42
4.3.2 Secondary Data	43
4.4 VISSIM Micro Simulation Platform.....	43
CHAPTER 5 VISSIM MICRO SIMULATION.....	46
5.1 Introduction	46
5.2 Signalized Intersection (Existing Condition).....	46
5.2.1 Geometric Data	46
5.2.2 VISSIM Input Data for Signalized Intersection.....	49
5.2.3 Calibration and Validation	55
5.3 Modern Roundabout.....	59
5.3.1 Link-Connector and Routing Decision	59
5.3.2 Priority Rules and Reduced Speed Zone.....	62
5.3.3 Calibration and Validation	63
CHAPTER 6 RESULT AND ANALYSIS	65
6.1 Introduction.....	65
6.2 Results of Micro Simulation by VISSIM.....	65
6.2.1 Average Travel Delay	65
6.2.2 Average Travel Time	68
6.2.3 Average Approach Speed.....	72
6.3 Hypothesis Analysis : Paired Sample T-test	75



CHAPTER 7 CONCLUSION AND RECOMMENDATION	80
7.1 Conclusion.....	80
7.2 Recommendation.....	81
REFERENCES	
APPENDIXES	

List of Tables

Table 3.1 Properties of Car Following Model	36
Table 3.2 The Rules from GEH Result	37
Table 5.1 Vehicle Type Composition	50
Table 5.2 Vehicle Composition by Origin and Destination	53
Table 5.3 Default and Calibrated Values for VISSIM	56
Table 5.4 GEH Result of Traffic Volume data at morning peak hour	58
Table 5.5 GEH Result of Traffic Volume Data for afternoon Peak Hour	58
Table 5.6 Calculating Sample of RMSNE	59
Table 5.7 Geometric Data of Modern Roundabout Design	60
Table 5.8 GEH Result for Morning Data in Pelem Gurih Roundabout	63
Table 5.9 GEH Result for Afternoon data in Pelem Gurih Roundabout	64
Table 6.1 Average Travel Delay at morning peak hour	66
Table 6.2 Average Travel Delay at Afternoon Peak Hour	68
Table 6.3 Average Travel Time at Morning Peak Hour	69
Table 6.4 Average Travel Time at Afternoon Peak Hour	71
Table 6.5 Average Approach Speed in Morning Peak hour	73
Table 6.6 Average Approach Speed in Afternoon Peak Hour	74
Table 6.7 Percentage of Improvement in Converting Signalized Intersection to	

Modern Roundabout.....	75
Table 6.8 Delay Analysis for Paired t-test	76
Table 6.9 Paired Sample test result of average delay.....	77
Table 6.10 Travel Time Analysis for Paired t-test.....	77
Table 6.11 Paired sample test result of average travel time.....	78
Table 6.12 Approach Speed Analysis for Paired t-Test.....	78
Table 6.13 Paired Sample test result for approach Speed	79

List of Figures

Figure 1.1 Map of Special Region of Yogyakarta Province, Indonesia.....	2
Figure 1.2 Location of Pelem Gurih Intersection.....	2
Figure 2.1 Conflicts at Signalized Intersection and Roundabout.....	16
Figure 3.1 Inscribed circle diameter at normal roundabout	20
Figure 3.2 Approach Half Width and Entry width.....	22
Figure 3.3 Average Effective Flare Length.....	22
Figure 3.4 Entry Angle at Larger roundabout	24
Figure 3.5 Entry Angle at Smaller Roundabout.....	24
Figure 3.6 Entry curb radius.....	25
Figure 3.7 Entry Path Radius	26
Figure 3.8 Typical Single Carriageway Exits	27
Figure 3.9 Definition of Priority Rules	32
Figure 4.1 Research Process	40
Figure 4.2 Case Study Location	41
Figure 4.3 VISSIM Simulation Process	44
Figure 5.1 Google Earth capture of Pelem Gurih Intersection.....	47
Figure 5.2 Pelem Gurih Intersection Existing Condition.....	47
Figure 5.3 VISSIM Drawing for Existing Condition.....	49
Figure 5.4 Vehicle Static Routes for Signalized Intersection at VISSIM.....	51
Figure 5.5 Speed Cumulative Frequency of Vehicles in Morning Peak hour	52
Figure 5.6 Signal Timing at morning and afternoon peak hour	54
Figure 5.7 Traffic Signal at VISSIM Input for morning time.....	55
Figure 5.8 Driving Behavior in Indonesia at VISSIM	57

Figure 5.9 Modern Roundabout Design of Pelem Gurih Intesection.....	60
Figure 5.10 Link and Connector in VISSIM Modern Roundabout Design	61
Figure 5.11 Routing Decision of Modern Roundabout Model in VISSIM.....	62
Figure 5.12 Reduced Speed Area and Priority Rules for Roundabout	63
Figure 6.1 Average Travel Delay at South to North Leg and North to South leg in morning peak hour	66
Figure 6.2 Average Travel Delay South to North leg and North to South Leg in Afternoon Peak Hour	67
Figure 6.3 Average Travel Time at South to North Leg and North to South Leg in Morning Peak Hour.....	69
Figure 6.4 Average Travel Time at South to North Leg and North to South Leg at Afternoon Peak Hour	70
Figure 6.5 Average Approach Speed at South and North in the Morning Peak hour	72
Figure 6.6 Average Approach Speed at South and North in the Afternoon Peak Hour	72