

DAFTAR PUSTAKA

- Allegro. (2007). *Fully Integrated Hall Effect - Based Linear Current Sensor with 2.1 kVRMS Voltage Isolation and a Low-Resistance Current Conductor*.
MycroSystems Inc. Allegro MicroSystems, Inc.
- Boylestad, R. L., & Nashelsky, L. (1998). *Electronic Device and Circuit* (Ed. 7).
New Jersey: Prentice Hall.
- Cheng, K. W., Divakar, B. P., Wu, H., Ding, K., & Ho, H. F. (2011). Battery-
Management System (BMS) and SOC Development for Electrical
Vehicles. *IEEE Transactions on Vehicular Technology*, 60, hal. 76 - 88.
- Chun, C. Y., Baek, J., Seo, G.-s., Cho, B. H., Kim, J., Chang, I. K., et al. (2014).
Current Sensor-less State-of-Charge Estimation Algorithm for Lithium-Ion
Batteries Utilizing Filtered Terminal Voltage. *Elsevier Journal of Power
Source*, 255 - 263.
- Clean Energy Ministerial. (2013). *GLOBAL EV OUTLOOK: Understanding the
Electric Vehicle Landscape to 2020*. Clean Energy Ministerial.
- David Houcke. Diakses pada tanggal 14 Agustus 2015, dari Applications of
MATLAB: Ordinary Differential Equations (ODE):
<https://www.mccormick.northwestern.edu/docs/efirst/ode.pdf>
- Digilent. (2011). *chipKit Uno32 Board Reference Manual*. Pullman, WA:
Digilent, Inc.