

DAFTAR PUSTAKA

- Allahbakhsh, A., Mazinani, S., Reza, M., Sharif, F., 2013. Cure kinetics and chemorheology of EPDM / graphene oxide nanocomposites. *Thermochim. Acta* 563, 22–32.
- Altabhu, S.A.S., Tajaldin, M.A., 2020. Effect of Temperature and Curing Time on The Fabrication of Polysiloxane filled Silica Synthetic Via Casting and Compression Moulding Methods. *Third Int. Conf. Tech. Sci.* 28–30.
- Alwaan, I.M., 2018. Rheological characterization and modeling of vulcanization kinetics of natural rubber/starch blends. *J. Appl. Polym. Sci.* 135, 46347. <https://doi.org/10.1002/app.46347>
- Anandhan, M., Kaisare, N.S., Kannan, K., Varkey, B., 2012. Population balance model for vulcanization of natural rubber with delayed-action accelerator and prevulcanization inhibitor. *Rubber Chem. Technol.* 85, 219–243. <https://doi.org/10.5254/rct.12.89971>
- Arrillaga, A., Zaldua, A.M., Atxurra, R.M., Farid, A.S., 2007. Techniques used for determining cure kinetics of rubber compounds. *Eur. Polym. J.* 43, 4783–4799. <https://doi.org/10.1016/j.eurpolymj.2007.08.024>
- Bai, W., 2009. New application of crystalline cellulose in rubber composites (Dissertation). Oregon State University.
- Bardestani, R., Patience, G.S., Kaliaguine, S., 2019. Experimental methods in chemical engineering: specific surface area and pore size distribution measurements—BET, BJH, and DFT. *Can. J. Chem. Eng.* 97, 2781–2791. <https://doi.org/10.1002/cjce.23632>
- Bartholin, M., Guyot, A., 1975. Preparation of uniform silica spheres. *Colloid Polym. Sci.* 634, 623–634.
- Bergna, H.E., 1994. *Colloid chemistry of silica*. ACS Publication.
- Bohin, F., Manas-Zloczower, I., Feke, D.L., 1996. Kinetics of dispersion for sparse agglomerates in simple shear flows: Application to silica agglomerates in silicone polymers. *Chem. Eng. Sci.* 51, 5193–5204. [https://doi.org/10.1016/S0009-2509\(96\)00338-7](https://doi.org/10.1016/S0009-2509(96)00338-7)
- Boonmee, A., Jarukumjorn, K., 2020. Preparation and characterization of silica nanoparticles from sugarcane bagasse ash for using as a filler in natural rubber composites. *Polym. Bull.* 77, 3457–3472. <https://doi.org/10.1007/s00289-019-02925-6>
- Brinke, J.W., 2002. *Silica Reinforced Tyre Rubbers*.
- Bui, L.A.T., Chen, C.T., Hwang, C.L., Wu, W.S., 2012. Effect of silica forms in rice husk ash on the properties of concrete. *Int. J. Miner. Metall. Mater.* 19, 252–258. <https://doi.org/10.1007/s12613-012-0547-9>
- Bukit, N., Ginting, E.M., Pardede, I.S., Frida, E., Bukit, B.F., 2018. Mechanical properties of composite thermoplastic hdpe / natural rubber and palm oil boiler ash as a filler. *J. Phys. Conf. Ser.* 1120. <https://doi.org/10.1088/1742-6596/1120/1/012003>
- Burhin, H.G., 2002. Quality Control of Green Tyre compounds. *Kautschuk Gummi Kunststoffe* 175–182.
- Cai, X., Hong, R.Y., Wang, L.S., Wang, X.Y., Li, H.Z., Zheng, Y., Wei, D.G., 2009. Synthesis of silica powders by pressured carbonation. *Chem. Eng. J.* 151, 380–386. <https://doi.org/10.1016/j.cej.2009.03.060>
- Chen, W.F., Liew, J.Y.R., 2003. *The civil engineering handbook*, 2nd ed. CRC Press.
- Chiang, Y., Lian, H., Leo, S., Wang, S., Yamauchi, Y., Wu, K.C., 2011. Controlling Particle Size and Structural Properties of Mesoporous Silica Nanoparticles Using the Taguchi Method. *J. Phys. Chem.* 115, 13158–13165.
- Ciullo, P.A., Hewitt, N., 1999. *The rubber formulary*. Noyes Publication, New York.
- Deshpande, R., Hua, D.W., Smith, D.M., Brinker, C.J., 1992. Pore structure evolution in silica gel during aging/drying. III. Effects of surface tension. *J. Non. Cryst. Solids* 144, 32–44.

- Dileep, P., Narayanankutty, S.K., 2020. A novel method for preparation of nanosilica from bamboo leaves and its green modification as a multi-functional additive in styrene butadiene rubber. *Mater. Today Commun.* 24. <https://doi.org/10.1016/j.mtcomm.2020.100957>
- Dileep, P., Varghese, G.A., Sivakumar, S., Narayanankutty, S.K., 2020. An innovative approach to utilize waste silica fume from zirconia industry to prepare high performance natural rubber composites for multi-functional applications. *Polym. Test.* 81. <https://doi.org/10.1016/j.polymertesting.2019.106172>
- Dimier, F., Vergnes, B., Vincent, M., 2004. Relationships between mastication conditions and rheological behavior of a natural rubber. *Rheol. Acta* 43, 196–202. <https://doi.org/10.1007/s00397-003-0342-7>
- Dominic, M.C.D., Begum, P.M.S., Joseph, R., Joseph, D., Kumar, P., Ayswarya, E.P., 2013. Synthesis, characterization and application of rice husk nanosilica in natural rubber. *Int. J. Sci. Environ. Technol.* 2, 1027-1035.
- dos Santos, R.J., Agostini, D.L. da S., Cabrera, F.C., Reis, E.A.P. dos, Ruiz, M.R., Budenberg, E.R., Teixeira, S.R., Job, A.E., 2014. Sugarcane bagasse ash: New filler to natural rubber composite. *Polímeros* 24, 646–653.
- El-Sabbagh, S.H., Yehia, A.A., 2007. Detection of Crosslink Density by Different Methods for Natural Rubber Blended with SBR and NBR. *Egypt J. Solids* 30, 157–173.
- Esmizadeh, E., Naderi, G., Ghoreishy, M.H.R., Bakhshandeh, G.R., 2011. Chemical and physical properties of self-crosslinked poly(vinyl chloride)/nitrile rubber nanocomposites prepared by melt-mixing process. *J. Polym. Eng.* 31, 83–92. <https://doi.org/10.1515/POLYENG.2011.024>
- Feke, D.L., 2007. Shear-Induced Dispersion of Particle Agglomerates, in: *Granulation*.
- Frasca, D., 2016. Multilayer Graphene Rubber Nanocomposites. *Universitat Berlin*.
- Gao, G., Zou, H., Gan, S., Liu, Z., An, B., Xu, J., Li, G., 2009. Preparation and properties of silica nanoparticles from oil shale ash. *Powder Technol.* 191, 47–51. <https://doi.org/10.1016/j.powtec.2008.09.006>
- Ghasemi, I., Karrabi, M., Mohammadi, M., Azizi, H., 2010. Evaluating the effect of processing conditions and organoclay content on the properties of styrene-butadiene rubber/organoclay nanocomposites by response surface methodology. *Express Polym. Lett.* 4, 62–70. <https://doi.org/10.3144/expresspolymlett.2010.11>
- Ghorbani, F., Sanati, A.M., Maleki, M., 2015. Production of silica nanoparticles from rice husk as agricultural waste by environmental friendly technique. *Environ. Stud. Persian Gulf* 2, 56–65.
- Ghosh, P., Katore, S., Patkar, P., Caruthers, J.M., 2003. Sulfur Vulcanization of Natural Rubber for Benzothiazole Accelerated Formulations. *Rubber Chem. Technol.* 76, 592–693.
- Han, Y.-S., Jeong, G.-Y., Lee, S.-Y., Kim, H.-K., 2007. Hematite template route to hollow-type silica spheres. *J. Solid State Chem.* 180, 2978–2985. <https://doi.org/10.1016/j.jssc.2007.08.016>
- Haryanto, H., 2017. Limbah Abu Bagas PT. Madukismo (Komunikasi Personal).
- Hasan, A., 2013. Studi proses mastikasi dan penggilingan karet alam: Pengaruhnya terhadap karakteristik vulkanisasi dan sifat fisik vulkanisat (Disertasi). Universitas Gadjah Mada.
- Hassan, A.F., Abdelghny, A.M., Elhadidy, H., Youssef, A.M., 2014. Synthesis and characterization of high surface area nanosilica from rice husk ash by surfactant-free sol – gel method. *J. Sol-Gel Sci. Technol* 69, 465–472. <https://doi.org/10.1007/s10971-013-3245-9>
- Hayichelaeh, C., Reuvekamp, L.A.E.M., Dierkes, W.K., Blume, A., Noordermeer, J.W.M., Sahakaro, K., 2018. Enhancing the silanization reaction of the silica-silane system by different amines in model and practical silica-filled natural rubber compounds. *Polymers (Basel)*. 10. <https://doi.org/10.3390/polym10060584>

- He, S., Hu, J., Zhang, C., Wang, J., Chen, L., Bian, X., Lin, J., 2018. Performance improvement in nano-alumina filled silicone rubber composites by using vinyl tri-methoxysilane. *Polym. Test.* 67, 295–301.
- Heideman, G., Datta, R.N., Noordermeer, J.W.M., van Baarle, B., 2004. Activators in Accelerated Sulfur Vulcanization. *Rubber Chem. Technol.* 77, 512–541. <https://doi.org/10.5254/1.3547834>
- Hewitt, N., 2007. Compounding Precipitated Silica in Elastomers. William Andrew Inc.
- Huabcharoen, P., Wimolmala, E., Markpin, T., Sombatsompop, N., 2017. Purification and characterization of silica from sugarcane bagasse ash as a reinforcing filler in natural rubber composites. *BioResource* 12, 1228–1245.
- Ichazo, M.N., Albano, C., Hernández, M., González, J., Carta, A., 2008. Effects of particle size and size distribution on the mechanical properties of EPDM/silica vulcanizates. *Adv. Mater. Res.* 47-50 PART, 113–116. <https://doi.org/10.4028/www.scientific.net/amr.47-50.113>
- Idrus, S.S., Ismail, H., Palaniandy, S., 2011. Study of the effect of different shapes of ultrafine silica as fillers in natural rubber compounds. *Polym. Test.* 30, 251–259. <https://doi.org/10.1016/j.polymertesting.2010.10.002>
- Iler, R.K., 1978. The chemistry of silica. John Wiley & Sons, Inc., New York.
- Israelachvili, J.N., 2011. Intermolecular and Surface Forces. Academic Press. <https://doi.org/10.1016/B978-0-12-375182-9.10014-4>
- Jang, S.-H., Kim, W.-S., Kang, Y.-G., Han, M.-H., Chang, S.-M., 2013. Study on Mixing Condition of the Rubber Composite Containing Functionalized S-SBR, Silica and Silane : II. Effect of Mixing Temperature and Time. *Elastomers Compos.* 48, 103–113. <https://doi.org/10.7473/EC.2013.48.2.103>
- Jang, S.H., Kim, W.S., Kang, Y.G., Han, M.H., Chang, S.M., 2013. Study on Mixing Condition of the Rubber Composite Containing Functionalized S-SBR, Silica and Silane: II. Effect of Mixing Temperature and Time. *Elastomers Compos.* 48, 103–113.
- Jeevanandam, J., Barhoum, A., Chan, Y.S., Dufresne, A., Danquah, M.K., 2018. Review on nanoparticles and nanostructured materials : history , sources , toxicity and regulations. *Beilstein J. Nanotechnol* 9, 1050–1074. <https://doi.org/10.3762/bjnano.9.98>
- Jeong, J.H., Moon, C.W., Leonov, A.I., Quirk, R.P., 2002. Cure kinetics for silane coupled silica filled SBR compounds. *Rubber Chem. Technol.* 75, 93–109. <https://doi.org/10.5254/1.3547676>
- Julie Chandra, C.S., Bipinbal, P.K., Sunil, K.N., 2017. Viscoelastic behaviour of silica filled natural rubber composites – Correlation of shear with elongational testing. *Polym. Test.* 60, 187–197. <https://doi.org/10.1016/j.polymertesting.2017.03.023>
- Julve, D., Menéndez, M., Pérez, J., Ramos, J., 2011. Microdispersion of silica in tire tread compounds above the percolation threshold by tem image measurements. *Rubber Chem. Technol.* 84, 74–87. <https://doi.org/10.5254/1.3544676>
- Kaewsakul, W., 2013. Silica-reinforced natural rubber for low rolling resistance, energy-saving tires. University of Twente.
- Kaewsakul, W., Sahakaro, K., Dierkes, W.K., Noordermeer, J.W.M., 2012. Optimization of Mixing Conditions for Silica-Reinforced Natural Rubber Tire Tread Compounds. *Rubber Chem. Technol.* 85, 277–294. <https://doi.org/10.5254/rct.12.88935>
- Kalapathy, U., Proctor, A., Shultz, J., 2000. A simple method for production of pure silica from rice hull ash 73.
- Kanking, S., Niltui, P., Wimolmala, E., Sombatsompop, N., 2012. Use of bagasse fiber ash as secondary filler in silica or carbon black filled natural rubber compound. *Mater. Des.* 41, 74–82. <https://doi.org/10.1016/j.matdes.2012.04.042>
- Kaptay, G., 2012. On the size and shape dependence of the solubility of nano-particle in solution. *Int. J. Pharm.* 430, 253–257.
- Kapur, R.S., Koenig, J.L., Shelton, J.R., 1974. Raman Spectral Studies of 2-

- Mercaptobenzothiazole Accelerator Systems. *Rubber Chem. Technol.* 47, 911–923. <https://doi.org/10.5254/1.3540473>
- Kenda, A., Eibl, O., Pongratz, P., 1999. Multiphase analysis with EDX elemental maps: Software implementation and application to (Bi,Pb)₂Sr₂Ca₂Cu₃O_(10+δ) high-T(c) superconducting tapes. *Micron* 30, 85–97. [https://doi.org/10.1016/S0968-4328\(98\)00033-X](https://doi.org/10.1016/S0968-4328(98)00033-X)
- Khan, M.I., Azizli, K., Sufian, S., Man, Z., SadaKhan, A., 2015. Simultaneous Preparation of Nano Silica and Iron Oxide from Palm Oil Fuel Ash and Thermokinetics of Template Removal. *R. Soc. Chem.* 5, 20788–20799. <https://doi.org/10.1039/x0xx00000x>
- Khang, T., Ariff, Z.M., 2012. Vulcanization kinetics study of natural rubber compounds having different formulation variables. *J. Therm. Anal. Calorim.* 109, 1545–1553. <https://doi.org/10.1007/s10973-011-1937-3>
- Kim, J.M., Chang, S.M., Kong, S.M., Kim, K., Kim, J., Kim, W., 2009. Control of hydroxyl group content in silica particle synthesized by the sol-precipitation process. *Ceram. Int.* 35, 1015–1019. <https://doi.org/10.1016/j.ceramint.2008.04.011>
- Kim, S.M., Nam, C.S., Kim, K.J., 2011. TMTD, MBTS, and CBS Accelerator Effects on a Silica Filled Natural Rubber Compound upon Vulcanization Properties. *Appl. Chem. Eng.* 22, 144–148.
- Kok, C.M., 1987. The effects of compounding variables on the reversion process in the sulphur vulcanization of natural rubber. *Eur. Polym. J.* 23, 611–615. [https://doi.org/10.1016/0014-3057\(87\)90006-1](https://doi.org/10.1016/0014-3057(87)90006-1)
- Kumar, A., Gupta, R.K., 2003. *Fundamentals of polymer engineering*. Marcell Dekker, Inc.
- Kumar, N.R., Roy, S., Gupta, B.R., Bhowmick, A.K., 1992. Structural changes in rubber during milling. *J. Appl. Polym. Sci.* 45, 937–945. <https://doi.org/10.1002/app.1992.070450601>
- Lagaly, G., Tufar, W., Minihan, A., Lovell, A., 2012. Silicates, in: *Ullmann's Encyclopedia of Industrial Chemistry*. pp. 509–572. <https://doi.org/10.1002/14356007.a23>
- Lee, Y.S., Hwang, K.S., Lee, J.C., Kim, T.G., Ha, K.R., 2011. Effect of TESPT Silane Coupling Agent on Mechanical Properties of Precipitated Silica Filled NBR Compound for Oil Seal. *Elastomer Compos.* 46, 45–53.
- Leksomboon, A., Jongsomjit, B., 2011. Synthesis of spherical silica by sol-gel method and its application as catalyst support. *ASEAN J. Chem. Eng.* 10, 25. <https://doi.org/10.22146/ajche.50086>
- Leroy, E., Souid, A., Deterre, R., 2013. A continuous kinetic model of rubber vulcanization predicting induction and reversion. *Polym. Test.* 32, 575–582.
- Li, J., Gong, X., Zhu, H., Jiang, W., 2009. Influence of particle coating on dynamic mechanical behaviors of magnetorheological elastomers. *Polym. Test.* 28, 331–337. <https://doi.org/10.1016/j.polymertesting.2009.01.008>
- Li, J., Qian, T., Tong, L., Shen, J., 2014. Preparation and Characterization of Nanosilica from Oil Shale Ash. *J. Nanosci. Nanotechnol.* 14, 3884–3886. <https://doi.org/10.1166/jnn.2014.7941>
- Li, Y., Han, B., Wen, S., Lu, Y., Yang, H., Zhang, L., Liu, L., 2014. Effect of the temperature on surface modification of silica and properties of modified silica filled rubber composites. *Compos. Part A* 62, 52–59.
- Liang, J., Feng, N., Chang, S., Wang, C.X., Zhang, G., 2013. EFFECT OF POLYSULFANE SILANIZED SILICA ON THE MORPHOLOGY AND MECHANICAL PROPERTIES OF BROMBUTYL RUBBER VULCANIZATES. *Rubber Chem. Technol.* 86, 558–571. <https://doi.org/10.5254/rct.13.87960>
- Liou, T.-H., Yang, C.-C., 2011. Synthesis and surface characteristics of nanosilica produced from alkali-extracted rice husk ash. *Mater. Sci. Eng. B* 176, 521–529. <https://doi.org/10.1016/j.mseb.2011.01.007>
- Liou, T., Yang, C., 2011. Synthesis and surface characteristics of nanosilica produced from alkali-extracted rice husk ash. *Mater. Sci. Eng. B* 176, 521–529.

- Lolage, M., Parida, P., Chaskar, M., Gupta, A., Rautaray, D., 2020. Green Silica: Industrially scalable & sustainable approach towards achieving improved “nano filler – Elastomer” interaction and reinforcement in tire tread compounds. *Sustain. Mater. Technol.* 26. <https://doi.org/10.1016/j.susmat.2020.e00232>
- Lopez-Esparza, R., Altamirano, M.A.B., Perez, E., Goicochea, A.G., 2015. Importance of Molecular Interactions in Colloidal Dispersions. *Adv. Condens. Matter Phys.* 683716, 1–8. <https://doi.org/10.1155/2015/683716>
- Manchanda, C.K., Khaiwal, R., Mor, S., 2017. Application of sol–gel technique for preparation of nanosilica from coal powered thermal power plant fly ash. *J. Sol-Gel Sci. Technol.* 83, 574–581. <https://doi.org/10.1007/s10971-017-4440-x>
- Marin, R.R.R., Babick, F., Lindner, G., Wiemann, M., Stintz, M., 2018. Effects of sample preparation on particle size distributions of different types of silica in suspensions. *Nanomaterials* 8, 454. <https://doi.org/10.3390/nano8070454>
- Maskara, A., Smith, D.M., 1997. Agglomeration during the Drying of Fine Silica Powder, Part II: The Role of Particle Solubility. *J. Am. Ceram. Soc.* 80, 1715–1722.
- Megawati, M., Fardhyanti, D.S., Putri, R.D.A., Fianti, O., Simalango, A.F., Akhir, A.E., 2018. Synthesis of silica powder from sugar cane bagasse ash and its application as adsorbent in adsorptive-distillation of ethanol-water solution, in: *MATEC Web of Conferences*. pp. 1–6.
- Meng, X., Zhang, Y., Lu, J., Zhang, Z., Liu, L., Chu, P.K., 2013. Effect of Bamboo Charcoal Powder on the Curing Characteristics, Mechanical Properties, and Thermal Properties of Styrene – Butadiene Rubber with Bamboo Charcoal Powder. *J. Appl. Polym. Sci.* 4534–4541. <https://doi.org/10.1002/app.39522>
- Merget, R., Bauer, T., Küpper, H., Philippou, S., Bauer, H., Breitstadt, R., Bruening, T., 2002. Health hazards due to the inhalation of amorphous silica. *Arch. Toxicol.* 75, 625–634. <https://doi.org/10.1007/s002040100266>
- Mizele, J., Dandurand, J.L., Schott, J., 1985. Determination of the surface energy of amorphous silica from solubility measurement in micropores. *Surf. Sci.* 162, 830–837.
- Mohamad, N., Yaakub, J., Abd Razak, J., Yaakob, M.Y., Shueb, M.I., Muchtar, A., 2014. Effects of epoxidized natural rubber (ENR-50) and processing parameters on the properties of NR/EPDM blends using response surface methodology. *J. Appl. Polym. Sci.* 131, 1–8. <https://doi.org/10.1002/app.40713>
- Mounir, R., Raslan, H.A., Mohamed, M.A., 2020. Impact of Gamma Radiation and Rice Husk Nanosilica on the Physico-Mechanical Properties of Styrene Butadiene Rubber/Natural Rubber Blend. *Polym. Bull.* <https://doi.org/10.1007/s00289-020-03303-3>
- Mullin, J.W., 2001. *Crystallization*, 4th ed. Butterworth-Heinemann.
- Musgo, J., Echeverría, J.C., Estella, J., Laguna, M., Garrido, J.J., 2009. Ammonia-catalyzed silica xerogels: Simultaneous effects of pH, synthesis temperature, and ethanol:TEOS and water:TEOS molar ratios on textural and structural properties. *Microporous Mesoporous Mater.* 118, 280–287. <https://doi.org/10.1016/j.micromeso.2008.08.044>
- Music, S., Filipovic-Vincekovic, N., Sekovanic, L., 2011. Precipitation of amorphous SiO₂ particles and their properties. *Brazilian J. Chem. Eng.* 28, 89–94.
- Narongthong, J., Sae-Oui, P., Sirisinha, C., 2018. Effects of mixing parameters and their interactions on properties of carbon black filled styrene-butadiene rubber. *Rubber Chem. Technol.* 91, 521–536. <https://doi.org/10.5254/rct.18.82581>
- Noor-ul-Amin, Faisal, M., Muhammad, K., Gul, S., 2016. Synthesis and characterization of geopolymer from bagasse bottom ash, waste of sugar industries and naturally available china clay. *J. Clean. Prod.* 129, 491–495. <https://doi.org/10.1016/j.jclepro.2016.04.024>
- Noushad, M., Ab Rahman, I., Che Zulkifli, N.S., Husein, A., Mohamad, D., 2014. Low surface area nanosilica from an agricultural biomass for fabrication of dental nanocomposites. *Ceram. Int.* 40, 4163–4171. <https://doi.org/10.1016/j.ceramint.2013.08.073>

- Oldhuis, M., 2020. Relevance and development of new rubber technology competences for a sustainable automotive industry. University of Twente.
- Osman, N.S., Sapawe, N., 2020. Materials Today : Proceedings Optimization of silica (SiO_2) synthesis from acid leached oil palm frond ash (OPFA) through sol-gel method 31, 232–236.
- Pa, F.C., Chik, A., Bari, M.F., 2016. Palm Ash as an Alternative Source for Silica Production. MATEC Web Conf. 78. <https://doi.org/10.1051/mateconf/20167801062>
- Pacek, A.W., Ding, P., Utomo, A.T., 2007. Effect of energy density, pH and temperature on de-aggregation in nano-particles/water suspensions in high shear mixer. Powder Technol. 173, 203–210. <https://doi.org/10.1016/j.powtec.2007.01.006>
- Pangamol, P., Malee, W., Yujaroen, R., Sae-Oui, P., Siri Wong, C., 2018. Utilization of Bagasse Ash as a Filler in Natural Rubber and Styrene–Butadiene Rubber Composites. Arab. J. Sci. Eng. 43, 221–227. <https://doi.org/10.1007/s13369-017-2859-6>
- Pattanawanidchai, S., Loykulnant, S., Sae-Oui, P., Maneevas, N., Sirisinha, C., 2014. Development of eco-friendly coupling agent for precipitated silica filled natural rubber compounds. Polym. Test. 34, 58–63. <https://doi.org/10.1016/j.polymertesting.2014.01.002>
- Pattanawanidchai, S., Sae-Oui, P., Sirisinha, C., Siri Wong, C., 2019. Cure retardation of peroxide-cured silica filled natural rubber influenced by organosilane. Polym. Eng. Sci. 59, 42–48.
- Philbert, P., Surya, I., 2020. Influences of Modified Palm Stearin on Vulcanization Properties of Carbon Black-Loaded Epoxidized Natural Rubber Influences of Modified Palm Stearin on Vulcanization Properties of Carbon Black-Loaded Epoxidized Natural Rubber, in: IOP Conference Series: Materials Science and Engineering PAPER. <https://doi.org/10.1088/1757-899X/1003/1/012123>
- Phrommedetch, S., Pattamaprom, C., 2010. Compatibility Improvement of Rice Husk and Bagasse Ashes with Natural Rubber by Molten-State Maleation. Eur. J. Sci. Res. 43, 411–416.
- Quarch, K., Kind, M., 2010. Inorganic Precipitated Silica Gel. Part 1: Gelation Kinetics and Gel Properties. Chem. Eng. Technol. n/a-n/a. <https://doi.org/10.1002/ceat.201000080>
- Rafiee, E., Shahebrahimi, S., Feyzi, M., Shaterzadeh, M., 2012. Optimization of synthesis and characterization of nanosilica produced from rice husk (a common waste material). Int. Nano Lett. 2, 1–8.
- Ragueh, D.M., Meireles, M., Cabane, B., Gummel, J., 2015. Filtration of precipitated silica aggregates: Length scales, percolation threshold and yielding behaviour. Sep. Purif. Technol. 156, 2–11. <https://doi.org/10.1016/j.seppur.2015.10.005>
- Rajan, R., Varghese, S., Balachandran, M., George, K.E., 2016. Response surface methodology: a tool for assessing the role of compounding ingredients in peroxide vulcanization of natural rubber. Rubber Chem. Technol. 89, 211–226.
- Raza, N., Raza, W., Madeddu, S., Agbe, H., Kumar, R. V., Kim, K., 2018. Synthesis and characterization of amorphous precipitated silica from alkaline dissolution of olivine. RSC Adv. 8, 32651–32658. <https://doi.org/10.1039/c8ra06257a>
- Roshanaei, H., Khodkar, F., Alimardani, M., 2020. Contribution of filler–filler interaction and filler aspect ratio in rubber reinforcement by silica and mica. Iran. Polym. J. (English Ed. 29, 901–909. <https://doi.org/10.1007/s13726-020-00850-4>
- Ryu, C., Yang, J., Park, W., Kim, S.J., Kim, D. Il, Seo, G., 2020. Silica-filled NR compounds prepared by dry and wet masterbatches with different mixing times. J. Appl. Polym. Sci. 49548. <https://doi.org/10.1002/app.49548>
- Sae-oui, P., Rakdee, C., Thanmathorn, P., 2002. Use of Rice Husk Ash as Filler in Natural Rubber Vulcanizates : In Comparison with Other Commercial Fillers. J. Appl. Polym. Sci. 2485–2493. <https://doi.org/10.1002/app.10249>
- Salavati-Niasari, M., Javidi, J., 2012. Sonochemical Synthesis of Silica and Silica Sulfuric Acid Nanoparticles from Rice Husk Ash: A New and Recyclable Catalyst for the Acetylation of

- Alcohols and Phenols Under Heterogeneous Conditions. *Comb. Chem. High Throughput Screen.* 15, 705–712. <https://doi.org/10.2174/138620712803519743>
- Sarawade, P.B., Kim, J., Hilonga, A., Viet, D., Taik, H., 2011. Effect of drying technique on the physicochemical properties of sodium silicate-based mesoporous precipitated silica. *Appl. Surf. Sci.* 258, 955–961. <https://doi.org/10.1016/j.apsusc.2011.09.035>
- Sarkawi, S.S., Dierkes, W.K., Noordermeer, J.W.M., 2013. The influence of non-rubber constituents on performance of silica reinforced natural rubber compounds. *Eur. Polym. J.* 49, 3199–3209. <https://doi.org/10.1016/j.eurpolymj.2013.06.022>
- Sattayanurak, S., Sahakaro, K., Kaewsakul, W., Dierkes, W.K., Reuvekamp, L.A.E.M., Blume, A., Noordermeer, J.W.M., 2020. Synergistic effect by high specific surface area carbon black as secondary filler in silica reinforced natural rubber tire tread compounds. *Polym. Test.* 81. <https://doi.org/10.1016/j.polymertesting.2019.106173>
- Schilde, C., Gothsch, T., Quarch, K., Kind, M., Kwade, A., 2009. Effect of important precipitation process parameters on the redispersion process and the micromechanical properties of precipitated silica. *Chem. Eng. Technol.* 32, 1078–1087. <https://doi.org/10.1002/ceat.200900023>
- Schlomach, J., Kind, M., 2004. Investigations on the semi-batch precipitation of silica. *J. Colloid Interface Sci.* 277, 316–326. <https://doi.org/10.1016/j.jcis.2004.04.051>
- Seangyen, W., Prapainainar, P., Sae-Oui, P., Loykulnant, S., Dittanet, P., 2018. Natural rubber reinforced with silica nanoparticles extracted from jasmine and riceberry rice husk ashes. *Mater. Sci. Forum* 936 MSF, 31–36. <https://doi.org/10.4028/www.scientific.net/MSF.936.31>
- Sert Çok, S., Koç, F., Balkan, F., Gizli, N., 2019. Revealing the pore characteristics and physicochemical properties of silica ionogels based on different sol-gel drying strategies. *J. Solid State Chem.* 278, 120877. <https://doi.org/10.1016/j.jssc.2019.07.038>
- Setyorini, I., Sarengat, N., Prayitno, P., Sugiharto, S., 2016. Pengolahan limbah cair industri lateks pekat dengan berbagai adsorben lokal. *Pros. Semin. Nas. Kulit, Karet Dan Plast.* ISSN: 2477, 207–216.
- Shahzamani, M., Bagheri, R., Masoomi, M., Haghighi, M., Dourani, A., 2017. Effect of drying method on the structure and porous texture of silica-polybutadiene hybrid gels : Supercritical vs . ambient pressure drying 460, 119–124.
- Shanmugaraj, A.M., Bhowmick, A.K., 2003. Dynamic mechanical properties of styrene-butadiene rubber vulcanizate filled with electron beam modified surface-treated dual-phase filler. *J. Appl. Polym. Sci.* 88, 2992–3004. <https://doi.org/10.1002/app.12067>
- Sheel, T.K., Poddar, P., Murad, A.B.M.W., Neger, A.J.M.T., Chowdhury, A.M.S., 2016. Preparation of aluminum oxide from industrial waste can available in Bangladesh environment : SEM and EDX analysis. *J. Adv. Chem. Eng.* 6. <https://doi.org/10.4172/2090-4568.1000152>
- Shen, M., Zhao, F., Wang, S., Zhao, S., 2013. Effect of Type and Load of Silica on Dynamic Properties of Solution Styrene-Butadiene Rubber / Butadiene Rubber. *J. Macromol. Sci. Part B* 52, 398–406. <https://doi.org/10.1080/00222348.2012.676436>
- Sheng, L., Zhang, Y., Tang, F., Liu, S., 2018. Microporous and Mesoporous Materials Mesoporous / microporous silica materials : Preparation from natural sands and highly efficient fixed-bed adsorption of methylene blue in wastewater 257.
- Shrestha, S., Wang, B., Dutta, P., 2020. Nanoparticle processing: Understanding and controlling aggregation. *Adv. Colloid Interface Sci.* 279. <https://doi.org/10.1016/j.cis.2020.102162>
- Singh, B., Polshettiwar, V., 2016. Design of CO₂ sorbents using functionalized fibrous nanosilica (KCC-1): insights into the effect of the silica morphology (KCC-1 vs MCM-41). *J. Mater. Chem. A*. 7005–7019. <https://doi.org/10.1039/c6ta01348a>
- Sittiphan, T., Prasassarakich, P., Poompradub, S., 2014. Styrene grafted natural rubber reinforced by in situ silica generated via sol-gel technique. *Mater. Sci. Eng. B Solid-State Mater. Adv. Technol.* 181, 39–45. <https://doi.org/10.1016/j.mseb.2013.11.018>

- Spyrogianni, A., Herrmann, I.K., Keepend, K., Pratsinis, S.E., Wegner, K., 2017. The silanol content and in vitro cytolytic activity of flame-made silica. *J. Colloid Interface Sci.* 507, 95–106.
- Sridharan, H., Guha, A., Bhattacharyya, S., Bhowmick, A.K., Mukhopadhyay, R., 2019. Effect of silica loading and coupling agent on wear and fatigue properties of a tread compound. *Rubber Chem. Technol.* 92, 326–349. <https://doi.org/10.5254/rct.18.81570>
- Srisuwan, L., Jarukumjorn, K., Suppakarn, N., 2018. Effect of Silane Treatment Methods on Physical Properties of Rice Husk Flour/Natural Rubber Composites. *Adv. Mater. Sci. Eng.* 2018. <https://doi.org/10.1155/2018/4583974>
- Stephens, D.K., Wellen, C.W., Smith, J.B., Kubiak, K.F., 2002. US 6.375.735 B1: Precipitated silicas, silica gels with and free of deposited carbon from caustic biomass ash solutions and processes. US 6375735 B1.
- Subbukrishna, D.N., Suresh, K.C., Paul, P.J., Dasappa, S., Rajan, N.K.S., 2007. Precipitated silica from rice husk ash by IPSIT process. 15th Eur. Biomass Conf. Exhib. 7–11.
- Suliman, M.E., Almola, S.M.F., 2011. The use of sugarcane bagasse ash as an alternative local pozzolanic material: study of chemical composition. *Sci. Vis.* 16, 65–69.
- Sussman, G.L., Frpc, C., Beezhold, D.H., 2000. Allergens and natural rubber proteins. *J. Allergy Clin. Immunol.* 33–39. <https://doi.org/10.1067/mai.2002.124969>
- Tapu, M.I., 2018. Cost-Effective Synthesis of High Purity Precipitated Silica From Locally Available Rice. Bangladesh University of Engineering and Technology.
- Thanh, N.T.K., Maclean, N., Mahiddine, S., 2014. Mechanisms of nucleation and growth of nanoparticles in solution. *Chem. Rev.* 114, 7610–7630. <https://doi.org/10.1021/cr400544s>
- Thaworn, K., Buahom, P., Areerat, S., 2012. Effects of Organic Peroxides on the Curing Behavior of EVA Encapsulant Resin. *Open J. Polym. Chem.* 2012, 77–85.
- Thommes, M., Kaneko, K., Neimark, A. V., Olivier, J.P., Rodriguez-Reinoso, F., Rouquerol, J., Sing, K.S.W., 2015. Physisorption of gases, with special reference to the evaluation of surface area and pore size distribution (IUPAC Technical Report). *Pure Appl. Chem.* 87, 1051–1069. <https://doi.org/10.1515/pac-2014-1117>
- Tognonvi, M.T., Soro, J., Gelet, J.L., Rossignol, S., 2012. Physico-chemistry of silica / Na silicate interactions during consolidation. Part 2: Effect of pH. *J. Non. Cryst. Solids* 358, 492–501. <https://doi.org/10.1016/j.jnoncrysol.2011.11.005>
- Torres Agredo, J., Mejía de Gutiérrez, R., Escandón Giraldo, C.E., González Salcedo, L.O., 2014. Characterization of sugar cane bagasse ash as supplementary material for Portland cement. *Ing. e Investig.* 34, 5–10. <https://doi.org/10.15446/ing.investig.v34n1.42787>
- Torres, G.B., Guilhermi, T., Deuber, D., Agostini, S., José, R., Camargo, F., Carlos, C., Gutierrez, M., Fabio, A., Guedes, F., Silvio, D.P., Teixeira, R., 2021. Potential Eco - friendly Application of Sugarcane Bagasse Ash in the Rubber Industry. *Waste and Biomass Valorization*.
- Utama, P.S., Yamsaengsung, R., Sangwichien, C., 2019. Production and characterization of precipitated silica from palm oil mill fly ash using CO₂ impregnation and mechanical fragmentation. *Brazilian J. Chem. Eng.* 36, 523–530. <https://doi.org/10.1590/0104-6632.20190361s20170458>
- Waddell, W.H., Evans, L.R., Lee, S., Lin, T.Y., Wu, C.S., 2018. Quantitative silica-filled tread dispersion rating system. *Rubber Plast. News* 16–21.
- Wijesinghe, H.G.I.M., Gamlath, G.R.V.S., Senevirathna, A.M.W.K., Edirisinghe, D.G., Wadugodapitiya, R.R.W.M.U.G.K., Bandara, T.A.R.W.M.M.C.G., Bandara, B.S.N., 2021. Effect of Pre-Blending and Phase-Mixing Methods on Properties of Natural Rubber and Acrylonitrile Butadiene Rubber Blends Filled with Nano Silica Extracted from Rice Husk Ash. *J. Nanosci. Technol.* 7, 928–932. <https://doi.org/10.30799/jnst.319.21070101>
- Witoon, T., Chareonpanich, M., 2012. Interaction of chitosan with tetraethyl orthosilicate on the formation of silica nanoparticles: Effect of pH and chitosan concentration. *Ceram. Int.* 38, 5999–6007. <https://doi.org/10.1016/j.ceramint.2012.04.056>

- Yan, H., Sun, K., Zhang, Yong, Zhang, Yinxi, 2004. Effects of mixing conditions on the reaction of 3-octanoylthio-1-propyltriethoxysilane during mixing with silica filler and natural rubber. *J. Appl. Polym. Sci.* 94, 2295–2301. <https://doi.org/10.1002/app.21153>
- Yantaboot, K., Amornsakchai, T., 2017. Effect of mastication time on the low strain properties of short pineapple leaf fiber reinforced natural rubber composites. *Polym. Test.* 57, 31–37. <https://doi.org/10.1016/j.polymertesting.2016.11.006>
- Yeoh, O.H., 2012. Mathematical modeling of vulcanization characteristic. *Rubber Chem. Technol.* 85, 482–492.
- Zawawi, E.Z.E., Ahmad, S., Rasid, R., 2012. Effect of melt-blending conditions on the properties of HDPE/NRBlends/ organoclay nanocomposites. *Adv. Mater. Res.* 576, 322–325. <https://doi.org/10.4028/www.scientific.net/AMR.576.322>
- Zhong, B., Jia, Z., Hu, D., Luo, Y., Jia, D., Liu, F., 2017. Enhancing interfacial interaction and mechanical properties of styrene-butadiene rubber composites via silica-supported vulcanization accelerator. *Compos. Part A Appl. Sci. Manuf.* 96, 129–136. <https://doi.org/10.1016/j.compositesa.2017.02.016>
- Zhu, Z., 2014. Theory on Orthokinetic Flocculation of Cohesive Sediment: A Review. *J. Geosci. Environ. Prot.* 02, 13–23. <https://doi.org/10.4236/gep.2014.25003>
- Zulkifli, N.S.C., Ab Rahman, I., Mohamad, D., Husein, A., 2013. A green sol–gel route for the synthesis of structurally controlled silica particles from rice husk for dental composite filler. *Ceram. Int.* 39, 4559–4567. <https://doi.org/10.1016/j.ceramint.2012.11.052>