

TABLE OF CONTENT

LEMBAR PENGESAHAN	i
PLAGIARISM-FREE STATEMENT	ii
ACKNOWLEDGEMENT	iii
TABLE OF CONTENT	iv
TABLE OF FIGURES	vi
TABLE OF TABLES	vii
TABLE OF ATTACHMENTS	viii
INTISARI	ix
ABSTRACT	x
CHAPTER I INTRODUCTION	1
1.1 Research background	1
1.2 Formulation of problem	2
1.3 Aims of research	3
1.4 Problem limitations	3
1.5 Benefit of research	3
CHAPTER II LITERATURE REVIEW	4
CHAPTER III THEORETICAL BASIS	8
3.1 Fluid mechanics	8
3.1.1. Reynolds number	8
3.1.2. Weber number	8
3.1.3. Womersley number	9
3.2 Dimensional analysis	9
3.3 Surface tension	11
3.4 Jurin's law about capillary action	12
3.5 Vibration	13
3.5.1. Vibration parameters	13
3.5.2. Natural frequencies and mode shapes	15
3.5.3. Sloshing in tanks, basins, and harbors	16

CHAPTER IV METHODOLOGY	18
4.1. Flow chart	18
4.2. Research location	19
4.3. Research material	19
4.4. Research equipment	19
CHAPTER V RESULTS AND DISCUSSIONS	25
5.1. Dimensional analysis	25
5.1.1. Direct ratio of transient inertial force and surface tension force .25	
5.1.2. Buckingham Pi Theorem (force, surface tension and viscosity) ...26	
5.2. Vibration measurement during interface instability	28
5.3. Force measurement	33
5.4. Surface tension measurement	35
5.5. The non dimensional number calculation	35
5.5.1. Direct ratio of transient inertial force and surface tension force .36	
5.5.2. Buckingham Pi Theorem (force, surface tension, and viscosity) ..39	
CHAPTER VI CONCLUSION	43
REFERENCES	44
APPENDIX	46